## **UNITED STATES**

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM 012709
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 30-6 Unit
	8. FARM OR LEASE NAME
1. oil gas X other	San Juan 30-6 Unit
	9. WELL NO.
2. NAME OF OPERATOR	15A \$ \$ \$ \$ \$ \$ \$ \$
EL PASO NATURAL GAS COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco MV
P.O. BOX 289, FARMINGTON, NEW MEXICO 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 29, T-30-N, R-7-W,
below.)	N.M.P.M. 5433
AT SURFACE: 1020' S, 1610' E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6311 G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF [] [X]	
FRACTURE TREAT	그 그 그 그 그 이 아이를 가는 그 있는 위치 함께 그 그
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	그 그 그 그 이 그 맛있습니다. 그는 일일도록 그래?
CHANGE ZONES	
ABANDON*	
(other)	그 그 그 하는 호흡환한 사람 (한국회의 중)
T DECORIDE PROPOSES OF SOUR ETER OPERATIONS	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent.	rectionally drilled give substitutes as lessalist
5-25-79: TD 3525'. Ran 93 jts. 7", 20#, K-55	intermediate each 25171
5-45-75. 10 5545 . Rail 55 JUS. 7", 20#, K-55	intermediate casing, 3513
set at 3525'. Cemented w/312 cu.ft. cement. W	OC 12 hrs, held 1200#/30 min.
Top of cement 2200'.	원 사용 영화 - 전 및 등 연호 용 기 및 등 인호 등 기 및 등 기 및 등 기 및 등 기 및 등 기 및 등 기 및 등 기 및 등 기 및 등 기 및 기 및
5-28-79: TD 5825'. Ran 80 jts. 4 1/2", 10.5#,	K-55 casing liner 2469! set
3356-5825'. Float collar set at 5809'. Cement	ed w/427 cit ft coment
WOC 18 hrs.	Cu w/ #2/ Cu.It. Cement.
NOC 10 H15.	
	± <b>/</b> 36 <b>3~</b> 43 ≥45ax\
	THE WONES REST

Subsurface Safety Valve: Manu. and Type \_ 18. I hereby certify that the foregoing is true and correct 5-31-79 Drilling Clerk DATE

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_\_CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

n str