OMITED SINIES	5. LEASE <u>မစ္စရိပ္ ပို</u> ရွိခါမွ ျပို
DEPARTMENT OF THE INTERIOR	SF079383 중국 및 설송된
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	🚽 🧎 អ៊ីសាស្ត្រស្រា
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
	San Juan 30-6 Unit
	8. FARM OR LEASE NAME
1. oil gas v	8. FARM OR LEASE NAME San Juan 30-6 Unit
well well other	9. WELL NO. \$128 - 2 5 5 5 7 100A \$555 5 5 6 5 7
2. NAME OF OPERATOR	100A SEE E EEE
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco MV
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 35, T-30-N, R-7-W
below.)	N.M.P.M.
AT SURFACE: 1610'N, 1180'W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	R.A. BASE N.M.
AT TOTAL DEPTH:	14. API NO. 22 7 3 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u></u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECUIEST FOR ADDROVAL TO. CURSTOLISM DEPORT OF	6847'GL含含量 第二章20
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	_372 · 5442
TEST WATER SHUT-OFF	전 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등
SHOOT OR ACIDIZE	<u> </u>
REPAIR WELL	(NOTE: Party of the second of
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9-330.):
MULTIPLE COMPLETE	
CHANGE ZONES	agentials alternate
ABANDON*	선 프로플로 및 함께를 했다.
(other)	ស្តី ស្ត្រី ស ស្ត្រី ស្ត្រី ស្ត្រ
(Val. 2.)	្ត
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertined.)	e all pertinent details, and give pertinent dates, lirectionally drilled, give subsurface locations and
6-23-79: Spudded well. Drilled surface hole.	Ran 5 ioints $9.5/8!!$ 36# K-55
surface casing 200' set at 212'. Cemented w/	
to surface. WOC 12 hours, held 600#/30 minute	
to Surface, wol 12 hours, herd out#/30 minute	▷• 의 의 의 의 의 의 의 기계 있다.

6-30-79: TD 4118'. Ran 105 joints, 7", 20#, K-55 intermediate casing, 4106' set at 4118'. Cemented w/408 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 2300'. 7-3-79: TD 6371'. Ran 81 joints, 4 1/2", 10.5#, K-55 casing liner, 2388! set

3983-6371'. Float collar set at 6354'. Cemented w/431 cu.ft. cement. WOC 18 hours.

C blund to the state of the control on order State t OIL CON. COM. Subsurface Safety Valve: Manu. and Type ____ of the list of the 18. I hereby ertify that the foregoing is true and correct DIST. 3 TITLE Drilling Clerk July

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

tion of the state ens 979 (ens) 97

U. S. GEOLOGICAL SURVEY DURANGO, COLO.