UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5. LE	ASE
SF	080713-B

	O.	00073	עייטו	,
6	IF	INDIAN	ALLOTTEE OR TRIBE	MANAE

	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 30-6 Unit
1 ail and	8. FARM OR LEASE NAME
1. oil gas 🗵 other	San Juan 30-6 Unit 9. WELL NO.
2. NAME OF OPERATOR	45A
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesa Verde
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 15, T-30-N, R-6-W
AT SURFACE: 1600'S, 990'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6399' G.L.
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zon
PULL OR ALTER CASING 🗌	change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent.	rectionally drilled give subsurface locations and
including estimated date of starting any proposed work. If well is di	rectionally drilled, give subsurface locations and to this work.)* oints 9 5/8". 36#. H-40 surface
including estimated date of starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths are starting	rectionally drilled, give subsurface locations and to this work.)* oints 9 5/8". 36#. H-40 surface
including estimated date of starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting any proposed work. If well is dispersional measured and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths for all markers and zones pertinent in the starting and true vertical depths are starting	rectionally drilled, give subsurface locations and to this work.)* oints 9 5/8", 36#, H-40 surface ft. cement. Circulated to OCT
including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinent in the start of the sta	rectionally drilled, give subsurface locations and to this work.)* points 9 5/8", 36#, H-40 surface ft. cement. Circulated to
including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinent. -79: Spudded well. Drilled surface hole. Ran 5 journament of the surface well. Casing 202' set at 215'. Cemented w/ 224 cu. surface. WOC 12 hours; held 600#/30 minutes. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	rectionally drilled, give subsurface locations and to this work.)* points 9 5/8", 36#, H-40 surface ft. cement. Circulated to
including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinent. -79: Spudded well. Drilled surface hole. Ran 5 journament of the surface well. Casing 202' set at 215'. Cemented w/ 224 cu. surface. WOC 12 hours; held 600#/30 minutes. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	rectionally drilled, give subsurface locations and to this work.)* Doints 9 5/8", 36#, H-40 surface ft. cement. Circulated to OCT OIL Set @ Set @ ClerkDATE Sept. 25, 1979
Including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinent. -79: Spudded well. Drilled surface hole. Ran 5 journers are casing 202' set at 215'. Cemented w/ 224 cu. surface. WOC 12 hours; held 600#/30 minutes. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct signed are correct.	rectionally drilled, give subsurface locations and to this work.)* Doints 9 5/8", 36#, H-40 surface ft. cement. Circulated to OCT OIL Set @ Set @ ClerkDATE Sept. 25, 1979

SEP 2 8 1979