

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1470'N, 1845'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 080711
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 30-6 Unit
8. FARM OR LEASE NAME
San Juan 30-6 Unit
9. WELL NO.
26A
10. FIELD OR WILDCAT NAME
Blanco M.V.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19, T-30-N, R-6-W
N.M.P.M.
12. COUNTY OR PARISH
R.A.
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6613'GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-23-79: Spudded well. Drilled surface hole. Ran 5 joints 9 5/8", 36#, K-55 surface casing 210' set @224'. Cemented w/224 cu.ft. cement. Circulated to surface. WOC 12 hours; held 600#/30 minutes.

6-30-79: TD 3861'. Ran 96 joints 7", 20#, K-55 intermediate casing, 3849' @ at 3861'. Cemented w/305 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 2600'.

7-3-79: TD 6210'. Ran 81 joints 4 1/2", 10.5#, K-55 casing liner, 2513' set 3697-6210'. Float collar set at 6194'. Cemented w/434 cu.ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Buies TITLE Drilling Clerk DATE July 5, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JUL 12 1979
GIL CO
D.S. GEOLOGICAL SURVEY
DURANGO, COLO.