1. oil well

below.)
AT SURFACE:

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)

other

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

820'S, 1500'E

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,

gas

well

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

 \mathbf{X}

El Paso Natural Gas Company

Box 289, Farmington, New Mexico

5.	LEASE - (
	SF080712A
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
7.	UNIT AGREEMENT NAME
	San Juan 30-6 Unit
8.	FARM OR LEASE NAME
	San Juan 30-6 Unit
9.	WELL NO.
	49A
10.	FIELD OR WILDCAT NAME
	Blanco Mesa Verde
11.	SEC., T., R., M., OR BLK. AND SURVEY OR
	AREA Sec. 27, T-30-N, R-6-W
	N.M.P.M.
12.	COUNTY OR PARISH 13. STATE
	Rio Arriba New Mexico
14.	API NO.
15.	ELEVATIONS (SHOW DF. KDB. AND WD)

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

6844' G.L

(other)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-25-79: Spudded well. Drilled surface hole. Ran 5 joints 9 5/8", 36#, KS surface casing 198' set at 212'. Cemented w/224 cu. ft. cement. Circulated to surface. WOC 12 hours; held 600#/30 minutes.

SUBSEQUENT REPORT OF:

Sept. 26, 1979

(This space for Federal or State office use)

APPROVED BY ______CONDITIONS OF APPROVAL, IF ANY:

SIGNED

Subsurface Safety Valve: Manu. and Type _

18. I hereby certify that the foregoing is true and correct

_____ DATE

TITLE Drilling Clerk DATE

*See Instructions on Reverse Side

SEP 2 8 1979