UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

6.	IF INDIAN, ALLOTTEE	OR TRIB	E NAME
	SF080180A	44.	ម៉ូស៊ី <i>ត</i>
Э.	LEASE	<u>⊆</u>	<u> </u>

さぎごさ

SUNDRY NOTICES AND REPORTS ON WELLS	7.				
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)					
	,				

7.	UNIT AGREEMENT NAME: San Juan 30-6 Unit	al, a. able red, a
0	FARM OR LEACE NAME (\$	-

rese	rvoir. L	Jse Forr	n 9–331-	C for s	uch proposals.)	
1.	oil well		gas well	\mathbf{Q}	other	

San Juan 30-6 Unit 9. WELL NO. of Bui 11771 60A

2. NAME OF OPERATOR Paso Natural Gas Company

10. FIELD OR WILDCAT NAME Series (Series Blanco MV 6

3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1850'S, 1190'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

11. SEC., T., R., \mathbf{M}_{ij}^{\perp} OR BLK. AND SURVEY OR AREA Sec 31, T-30-N; R-6-W

N.M.P.M. 13. STATE 12. COUNTY OR PARISH N.M. R.A. io it bagit bina bina 2,55 14. API NO. 5 5

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) 6830 'GL₃ S = 3.

rgantare.
To top of lot

9

REQUEST FOR APPROVAL	TO:	SUBSEQUENT	REPORT	OF:
TEST WATER SHUT-OFF		\(\overline{\ov		٠.,
FRACTURE TREAT		~		
SHOOT OR ACIDIZE		□:		
REPAIR WELL				
PULL OR ALTER CASING				
MULTIPLE COMPLETE				
CHANGE ZONES				
ABANDON*				
(other)				

Chipsol (Tepol ((NOTE: Report results of multiple completion or zone nolitisquit taliquan off admini off admini change on Form 9-330.) n bluorie fr. strb draice s bottem bu soit bus be

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 6-20-79: TD 4150'. Ran 105 joints 7", 20#, K-55 intermediate casing, 4138' set at 4150'. Cemented w/379 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. 在開發出 Top of cement 2400'. 6-23-79: TD 6385'. Ran 76 joints 4 1/2', 10.5#, K-55 casing liner; 2375's set

4010-6385'. Float collar set at 6368'. Cemented w/416 curft cement. WOC18 hours

pircable State n Se instructions.

1818 1818 1810

Š 101,00 100 m

Subsurface Safety Valve: Manu. and Type _

18. I hereby certify that the foregoing is true and correct

usco SIGNED.

TITLE Drilling Clerk DATE

July

etse, n ed off osals o

o isc **7**

) teho

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

meripos ni meripos nult meripos nult 5 1 11b9

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY DURANGO, COLO.