TEST WATER SHUT-OFF FRACTURE TREAT

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

SHOOT OR ACIDIZE REPAIR WELL

PODDA:

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF 080180 A		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 30-6 Unit 8. FARM OR LEASE NAME		
1. oil gas X other	San Juan 30-6 Unit 9. WELL NO.		
2. NAME OF OPERATOR	60A		
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Blanco MV		
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 31, T-30-N, R-6-W		
AT SURFACE: 1850'S, 1190'E	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico 14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6830 G.L.		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			

(NOTE: Report results of multiple completion or zone

U. S. GEOLOGICAL

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

X

8-3-79: PBTD 6368'. Tested casing to 3500#, OK. Perfed P.L. 6012,6018,6024,6030, 6036,6042,6055,6061,6067,6073,6106,6118,6137,6143,6184,6190,6206,6231,6240, 6271'W/1 SPZ. Fraced w/68,798# 20/40 sand, 146,000 gal. water. Flushed w/ 9912 gal. water.

8-4-79: Perfed C.H. & Men. 5562, 5588,5609,5618,5625,5632,5740,5746,5752,5894,5900, 5978' W/1SPZ. Fraced w/43,500# 20/40 sand, 87,000 gal. water. Flushed w/8736 gal. water.

Subsurface Safety Valve: Manu. and Typ	oe		Set @ F1
18. I hereby certify that the foregoing is	true and correct		
SIGNED Jany Sraafus	d TITLE Dril	ling Clerk DATE	August 7, 1979
	(This space for Federa	or State office (\$50)	
APPROVED BY	TITLE	DATE	경험 경기 얼마 하다.
		AUGIO ON CON. DIST.	1979
	*See Instructions	on Revers QUL CON.	OM / AUG 8 1979