Form Approve Budget Burgan No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 079	
CUNDRY MOTICES AND REPORTS On WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME NEBU Agrmt. No. 1, Sec. 929 8. FARM OR LEASE NAME	
3. ADI P 4. LOO belo AT AT AT	ME OF OPERATOR Blackwood & Nichols Co., Ltd. DRESS OF OPERATOR CO. Box 1237 Durango, Colorado 81301 CATION OF WELL (REPORT LOCATION CLEARLY. See space 17 ow.) SURFACE: 1590' F/SL - 790' F/EL TOP PROD. INTERVAL: Same TOTAL DEPTH: Same ECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, PORT, OR OTHER DATA	Northeast B1 9. WELL NO. 7A 10. FIELD OR WILDCAT! Blanco Mesaver 11. SEC., T., R., M., OR AREA I-21-30N 12. COUNTY OR PARISH Rio Arriba 14. API NO.	NAME de BLK. AND SURVEY OR -7W 13. STATE New Mexico
TEST W FRACTU SHOOT REPAIR PULL O MULTIP	OR ALTER CASING	6720 GL (NOTE: Report results of multiple completion or zone change on Form 9–330.)	
ITICI	SCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state luding estimated date of starting any proposed work. If well is deasured and true vertical depths for all markers and zones parting:	iractionally drilled give out	give pertinent dates, surface locations and
9-4-79	Ran 6 jts 9 5/8" 36.00# H-40 casing; 246' set at 259'; cemented with 200 sac class B cement with 1/4# flocele per sack, 2% CaCl ₂ . Cement circulated; tested 9 5/8" casing to 800 PSI for thirty minutes, held OK.		
9-9-79	Ran 101 jts 7" 23.00# K-55 casing; 3932' set at 3944'; cemented with 200 sacks Lite with 1/4# flocele per sack and 100 sacks class B with 2% CaCl ₂ , 1/4# flocele per sack. Nippled up, tested casing to 1000 PSI for thirty minutes, held OK.		
9~12-79	Ran 62 jts $4\frac{1}{2}$ " 10.50# k-55 casing; 2588' 6233'; top of liner at 3689'. Cemented wi 2% gel, 0.6% CFR, $1/4\#$ flocele per sack an versed out fifteen barrels cement.	th 300 sacks 50-50) Pozmix with
Subsurfa	ace Safety Valve: Manu. and Type	Set	@ Ft.
18 he	ereby certify that the foregoing is true and correct	ger pare 9_13_	-79
	(This space for Federal or State offi	ce use)	

(This space for Federal or State APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY: *See Instructions on Rev

SEP 1 4 1979

OIL CON. COM. DIST. 3

S. GEOLOGICAL SURVEY DURANGO, COLO.