5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SLIDVEY	SF 079483-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas x other	Carson
Well Well Galler	9. WELL NO.
2. NAME OF OPERATOR	#2 10. FIELD OR WILDCAT NAME
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	Basin Dakota
I -	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 7, T-30-N, R-4-W
AT SURFACE: 1470'S, 810'W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6692' G.L.
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE U	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
(other)	
including estimated date of starting any proposed work. If well is dire	to this work.)*
measured and true vertical depths for all markers and zones pertinent	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g	ed 8296,8302,8316,8322,8328
PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water.	ed 8296,8302,8316,8322,8328
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type	ed 8296,8302,8316,8322,8328 gal. water. Flushed w/5,550
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type	ed 8296,8302,8316,8322,8328 gal. water. Flushed w/5,550
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type	Set @Ft.
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type	Set @Ft.
measured and true vertical depths for all markers and zones pertinent : PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE (This space for Federal or State office)	Set @Ft. Ck DATEAugust 27, 1979
measured and true vertical depths for all markers and zones pertinent PBTD 8334'. Tested casing to 4000#, OK. Perfe W/1 SPZ. Fraced w/30,000# 40/60 sand, 49,000 g gal. water. Subsurface Safety Valve: Manu. and Type	Set @Ft. Ck DATEAugust 27, 1979