

NO. OF COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	5

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

API #30-039-22099

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-347-26	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Northwest Pipeline Corporation		San Juan 30-5 Unit
3. Address of Operator		9. Well No.
P.O. Box 90, Farmington, New Mexico 87401		#69
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER M 900 FEET FROM THE West LINE AND 850 FEET FROM		Robernador PC - ext
THE South LINE, SECTION 32 TOWNSHIP 30N RANGE 5W NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
6721' GR		Rio Arriba

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

### SUBSEQUENT REPORT OF:


REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input type="checkbox"/>	OTHER	<input checked="" type="checkbox"/> Drilling Operations

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Apr 25, 1980 to Apr 27, 1980 Drilling 7-7/8" hole to a depth of 2986'. Changed to a 6-3/4" hole at that depth.

4-28 & 29, 1980 3900' TD'ed @ 1400 hrs on 4-28-80. RU loggers. Hit bridge @ 618'. TIH w/ pipe & conditioned hole for 6 hrs. TOH Ran IES/GR, CNL/FDC/GR Logs. LDDP. Ran 128 jts (3885') of 2-7/8", 6.5#, J55, EUE set @ 3895' cmt'd w/ 150 sks 65/35 poz w/ 12% gel & 12.5# gilsonite/sk. Tailed w/ 150 sks Bl "B" w/ 6% gel & 10# gilsonite/sk. Displaced plug w/ 1 bbl acetic acid & 21.4 bbls wtr. Plug bumped & tested to 4000 psi, held OK @ 1900 hrs on 4-29-80. Wilson temp survey found top of cmt @ 2000'. PBTD @ 3775'. Rig released @ 2030 hrs 4-29-80.

NOW WAITING ON COMPLETION.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donna Brace TITLE Production Clerk DATE May 1, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT #3 DATE MAY 2 1980

CONDITIONS OF APPROVAL, IF ANY: