

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API # 30-039-22099

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-347-26	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		San Juan 30-5 Unit
3. Address of Operator		8. Farm or Lease Name
P.O. Box 90, Farmington, N.M. 87401		San Juan 30-5 Unit
4. Location of Well		9. Well No.
UNIT LETTER <u>M</u> , <u>900'</u> FEET FROM THE <u>West</u> LINE AND <u>850'</u> FEET FROM		#69
THE <u>South</u> LINE, SECTION <u>32</u> TOWNSHIP <u>30N</u> RANGE <u>5W</u> NMPM.		10. Field and Pool, or Wildcat
		Gobernador P.C.
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
6721' GR		Rio Arriba

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data


NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Change Zones

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set tubing stop at 3650'.
2. Pump 50 sx cement.
3. Follow with wiper plug and 100 gal 7-1/2% acedic acid.
4. Perfed (3592'-3612') with 1 shot per ft.
5. After 5000 gal pad of treated water, fraced perfs with 30,000# 10/20 sand.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank T. Chavez TITLE Sr. Production Engineer DATE August 7, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT 3 DATE AUG 8 1980

CONDITIONS OF APPROVAL, IF ANY:

