

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M


835' FSL, 580' FEL, Sec. 28, T-30-N, R-7-W, NMPM

200 JAN 10 1995: Lease Number
NM-02151

070 FARMINGTON, NM: If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit
Well Name & Number
San Juan 30-6 U #91A
API Well No.
30-039-22193
Field and Pool
Blanco Mesaverde
County and State
Rio Arriba Co, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

12-14-99 MIRU. ND WH. NU BOP. TOOH w/201 jts 2 3/8" tbg. TIH w/4 1/2" gauge ring to 5525'. TOOH. TIH w/4 1/2" CIBP, set @ 5500'. TOOH. SDON.

12-15-99 TIH to 5500'. Load hole, circ clean w/193 bbl wtr. PT csg to 500 psi/5 min, OK. Establish circ. Plug #1: pump 22 sx Class "B" neat cmt inside csg @ 5210-5500'. TOOH to 4561'. Establish circ. Plug #2: pump 12 sx Class "B" neat cmt inside csg @ 4403-4561'. TOOH to 4278'. Establish circ. Plug #3: pump 106 sx Class "B" neat cmt inside csg @ 3624-4278'. TOOH. TIH w/7" gauge ring to 3500'. TOOH. TIH, perf 3 sqz holes @ 3521'. TOOH. Establish injection w/11 bbl wtr. TIH w/7" cmt retainer, set @ 3463'. TOOH. TIH. SDON.

12-16-99 Establish injection. Plug #4: pump 37 sx Class "B" neat cmt outside 7" csg below cmt retainer @ 3421-3521'. Pump 20 sx Class "B" neat cmt inside csg above cmt retainer @ 3359-3463'. TOOH. TIH, perf 3 sqz holes @ 2980'. TOOH. Establish injection. TIH w/cmt retainer, set @ 2933'. TOOH. Establish injection. Plug #5: pump 87 sx class "B" neat cmt below cmt retainer outside csg @ 2675-2980'. Pump 60 sx Class "B" neat cmt inside csg @ 2622-2933'. TOOH. TIH, perf 3 sqz holes @ 1521'. TOOH. Establish injection. TIH w/7" cmt retainer, set @ 1466'. TOOH. Establish injection. Plug #6: pump 37 sx Class "B" neat cmt below cmt retainer outside csg @ 1421-1521'. Pump 20 sx Class "B" neat cmt inside csg above cmt retainer @ 1362-1466'. TOOH. SDON.
(Herman Lujan, BLM on location.)

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed
no

Title Regulatory Administrator Date 1/6/00

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____
CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JAN 10 2000

NMOC

FARMINGTON FIELD OFFICE

12-17-99 TIH, perf 3 sqz holes @ 384'. Load csg w/26 bbl wtr. Establish circ down csg & out bradenhead. Plug #7: pump 166 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Cmt at surface. Install dry hole marker w/25 sx Class "B" neat cmt. RD. Rig released. (Herman Lujan, BLM on location). Well plugged and abandoned 12-17-99.