

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1520'N, 720'W
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079485A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 30-4 Unit
8. FARM OR LEASE NAME
San Juan 30-4 Unit
9. WELL NO.
39
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-30-N, R-4-W
NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7105' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-5-80: Spudded well. Drilled surface hole. Ran 7 joints 9 5/8", 40#, 66-S surface casing 310' set at 312'. Cemented w/ 325 cu. ft. cement. Circ. to surface. WOC 12 hours; held 600#/30 minutes.
- 12-10-80: TD 4342'. Ran 103 joints 7" 23#, KS intermediate casing 4330' set at 4342'. Cemented w/ 370 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes.
- 12-16-80: TD 8626'. Ran 264 joints 4 1/2", 11.6#, KS & PS production casing 8614' set 8626'. Float collar set at 8618'. Cemented w/ 655 cu. ft. cement. WOC 18 hours. Top of cement at 3700'.
- 12-30-80: PBTD 8626'. Tested casing to 4000#, OK. Perfed; 8434, 8442, 8450, 8477, 8484, 8490, 8498, 8504, 8512, 8520, 8528' W/1 SPZ. Fraced w/ 95,000# 20/40 sand, 88,900 gal. wtr. Flushed w/

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.
5165 gal. wtr.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Enisco TITLE Drilling Clerk DATE December 17, 1980

(This space for Federal or State office use)

APPROVED ACCEPTED FOR RECORD TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JAN 21 1981

NMOCC

BY RW FARMINGTON DISTRICT

*See Instructions on Reverse Side