

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

800'N, 1930'W

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

SF 080711A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit

8. FARM OR LEASE NAME

San Juan 30-6 Unit

9. WELL NO.

58A

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T-30-N, R-6-W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6836' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-10-80: TD 4152'. Ran 97 joints 7", 20 & 23#, KE intermediate casing 4140' set at 4152'. cemented w/ 316 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes.

7-17-80: Found split in 7" casing. Set Bridge plug at 4115'. Cement Retainer at 3500'. squeezed 100 cu. ft. cement. WOC 18 hours.

7-21-80: Set Bridge Plug at 1st squeeze, set retainer at 3472'. Cemented w/ 354 cu. ft. cement.

7-27-80: TD 4233'. Ran 29 joints 5 1/2", 15.5#K-55 casing liner 888' set 3345-4233'. Float collar set at 4217'. Cemented w/ 89 cu. ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. J. Guiso TITLE Drilling Clerk DATE July 28, 1980

(This space for Federal or State office use)

ACCEPTED FOR RECORD _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

AUG 06 1980

FARMINGTON DISTRICT

BY BW

*See Instructions on Reverse Side