

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Blackwood & Nichols Co., Ltd.
3. ADDRESS OF OPERATOR
P. O. Box 1237, Durango, Colorado 81301
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 760' F/SL - 2240' F/EL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

RECEIVED
JUN 22 1981
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(other) Side Track abandoned drill collars

5. LEASE NM 013706-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NEBU Agrmt. #1, Sec. 929
8. FARM OR LEASE NAME
Northeast Blanco Unit
9. WELL NO.
24R
10. FIELD OR WILDCAT NAME
Blanco Mesaverde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
0-17-30N-7W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6269' GL



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to set a cement retainer in 7" casing at 3150' and fill 4 1/2" liner with cement, 3178' - 5283' plus open hole 5290' - 5450'. Set a whipstock in 7" casing at 3125' and mill window in 7" casing. Drill 6 1/4" hole to 5900' TD. Run a 4 1/2" liner 3000' - 5900'. Cement with 350 sacks 50-50 Pozmix with 2% gel, 0.6% CFR and 1/4# flocele per sack with 6 1/4# Gilsonite per sack. Sand-water fracture with 200,000 gals. water and 150,000 lbs. 20-40 sand in two stages.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DeLasso Loos TITLE District Manager DATE 6-19-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUN 30 1981

JAMES F. SIMS

*See Instructions on Reverse Side

NMOCC

BY

DeLasso Loos