UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	•	FORM	APP	ROVED	
	Budget	Bureau	No.	1004-0	15
•	Ехр	ires M	arch	31,1	993
			シレー	Y (1)	

BONEARO OF HAR	D PARANCELLER.	21.4				
SUNDRY NOTICES AND	5. Lease Designation and Serial Number					
Do not use this form for proposals t						
a different rese Use "APPLICATION FOR PERMIT	6. If Indian, Allottee or Tribe Name					
1. Oil Gas Cther		7. If Unit or CA, Agreement Designation				
	San Juan 30-5 Unit					
2. Phillips Petroleum Company	8. Well Name and No. San Juan 30-5 Unit \$99					
3. 5525 Hwy. 64, NBU 3004, Farmington, NM	9. API Well No. 30-039-23269					
4. Location of Well (Footage, Sec., T., R.	10. Field and Pool, or Exploratory Area Basin Dakota					
Unit A, 940' FNL & 1080' FEL Section 33, T-30-W, R-5-W	11. County or Parish, State					
		Rio Arriba County, New Mexico				
12. CHECK APPROPRIATE BOX(s) TO I	NDICATE NATURE OF NOTICE, REPORT,	OR OTHER DATA				
TYPE OF SUBMISSION		TYPE OF ACTION				
Notice of Intent	Abandonment	Change of Plans				
	Recompletion	New Construction				
Subsequent Report	Plugging Back	Non-Routine Fracturing				
	Casing Repair	Water Shut-Off				
Final Abandonment Notice	Altering Casing	Conversion to Injection				
	Other	Dispose Water				
	Comple	Report results of multiple completion on Well tion or Recompletion Report and hog (orm.)				
 Describe Proposed or Completed Operations (Cleawork. If well is directionally drilled, give subsu 	rly state all pertinent details, and give pertine rface locations and true vertical depths for all	ent dates, including estimate date of stating and proposed markers and zones pertinent to this work.				
This sundry supersedes the sundry dated						
Well will be abandoned in the following n	aanner	721				
- Set cast iron bridge plug at 8120		OH, G OM DH				
Fill wellbore with mudladen fluid. Mix 15 sxs Class B cement and set balanced plug from 6855' to 6755'.						
	- Mix 15 sxs Class B cement and set balanced plug from 6855' to 6755' Mix 15 sxs Class B cement and spot balanced plug from 5728' to 56 7 8'.					
Perf 4 holes at 3804'. Set 4-1/2" cement retainer at 3754'. Mix 79 sxs Class B cement and pump 54 sxs below						
retainer, then spot 25 sxs above retainer.						
- Perf 4 holes at 3185'. Set 4-1/2" cement retainter at 3135'. Mix 68 sxs Class B cement and pump 47 sxs below retainer, then spot 21 sxs above retainer.						
Perf 4 holes at 1706'. Set 4-1/2" cement retainer at 1656'. Mix 57 sxs Class B cement and pump 53 sxs below						
retainer, then spot 4 sxs above retainer. Perf 4 holes at 433'. Circulate 157 sxs to surface inside and outside 4-1/2" and 7" casings.						
Cut off casing, cap, place abandonment marker and restore location per BLM regulations.						
14. I hereby certify that the foregoing i						
Signed Wharly Ed Hasely	Title Environmental/Regulatory E	ngineer Date September 13, 1994				
(This space for Federal or State office us	e)					
•	m(r)	Data				
Approved by Conditions of approval, if any:	Title	Date				

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to mak Aan dipartment of a fen of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. A- DISTRICT MANAGER