

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTME

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-6178 FAX: (506) 334-6170 nnrd.state.nm.us/ocd/District III/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE

Operator_P	hillips Petro	oleum Co. 017	654Lease Na	ame <u>S</u>	an J	uan 31-6 Unit	Well No <u>53</u>
Location of	Well:Unit Letter	J_Sec	Twp_30N	Rge <u>^{6W}</u>	A	.PI # 30-0 <u>39-237</u>	44
	NAME OF RESE	RVOIR OR POOL	1 = -	F PROD. or Gas)	M	ETHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	Mesaverde			gas		flowing	tubing
Lower Completion	Dakota			gas		flowing	tubing
		PRE-F	LOW SHUT-II	N PRESSUR	E DA	ATA	
Upper Completion	Hour, date shut-in 12-4-00		Length of time s		1 .	ess. Psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in 12-4-00		Length of time : 3 days			ess Psig 853	Stabilized? (Yes or No)
		•	FLOW TE	ST NO. 1	· .		
Commenced at	(hour, date)*	·		Zone producing	· T	- :	
TIME (hour,date)	LAPSED TIME SINCE*	PRESS Upper Completion		PROD. ZON TEMP	€ RE		EMARKS
12/8/00	24 hrs	350	182			Upper SI; low	er flowing
12/9/00	48 hrs	353	152			Upper SI; low	er flowing
Production ra	ate during test						
Oil:		BOPD base	d on	Bbls. in	·	Hours	GravGOR
Gas:		MCF	PD; Tested th	nru (Orifice o	r Met	er):	
		MID-1	TEST SHUT-II	N PRESSUR	E DA	\TA	
Upper Completion	Hour, date shut-in		Length of time	shut-in	SIp	ress psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in		Length of time			ress. psig	Stabilized? (Yes or No)
•		•	(Continue or	n reverse side)			

FLOW TEST NO 2

	d at (hour, date)		Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	Upper Completion		PROD. ZONE	REMARKS	
					<u> </u>	
			· D. redica ana (s. inHo Orfice or Meter):	ursGravGOR	
Remarks:hereby certify	y that the inform DEC 13 2	nation herein cor	ntained is true an	d complete to the	bes of my knowledge. Petroleum Company	
hereby certify pproved ew Mexico Oil	y that the inform DEC 1 3 2	nation herein cor	ntained is true an Operator	d complete to the Phillips 1	Petroleum Company Jim Kennedy	
hereby certify pproved_ ew Mexico Oil	y that the inform DEC 132 Conservation Di	nation herein cor	ntained is true an Operator	d complete to the Phillips 1	bes of my knowledge.	

AKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oll well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).