

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-178	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Cinco Ltd.		State Pat
3. Address of Operator		9. Well No.
Box 451, Albuquerque, New Mexico, 87103		1
4. Location of well		10. Field and Pool, or Wildcat
UNIT LETTER D 060 FEET FROM THE North LINE AND 1100 FEET FROM		Blanco Mesa Verde
THE West LINE, SECTION 32 TOWNSHIP 30N RANGE 7W NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
6186' GR		Rio Arriba

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-17-86 Drilled 8 3/4" hole to TD of 3376'.
Ran 83 joints of 7", 20#, k-55, casing. 3361.37' set at 3374'.
Float collar at 3290'. Cemented with 165 sxs of 65/35 poz
with 3% gel, 10% salt, 10% calseal, and 12 1/2# gilsonite/sk.
(292 cuft). Followed with 75 sxs Class B with 3% CaCl and
1/4# flocele/sk.(89 cuft). Good circulation throughout job.
PD at 2:45 AM, 10/18/86.

WOC 12 hrs.

Pressure test casing and BOPE to 1000 psi/ 30 mins. Held okay.

Top of Cement by temperature survey was 2000'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Fitch TITLE for Cinco Ltd. DATE 10/29/86

APPROVED Original Signed by FRANK T. CHAVEZ

TITLE SUPERVISOR DISTRICT #3

CONDITIONS OF APPROVAL, IF ANY:

OCT 29 1986