		,	Form approved. Budget Bureau N	o. 1004–0135
orm 3160-5	3160-5 UNITED STATES SUBMIT IN TRIPLICATE (Other Instructions on the state of the s		Expires August 31, 1985	
Formerly 9-331) DEPARTMENT OF THE INTERIOR recognition			Jicarilla Contract 462	
	BUREAU OF LAND MANAGEMEN	T	6. IF INDIAN, ALLOTTER	
CUND	RY NOTICES AND REPORTS	ON WELLS	76. 15 INDIAN, ALLESTIC	02 12155 **2.25
	em for proposals to drill or to deepen or plug		Jicarilla Apac	che Tribe
Use "APPLICATION FOR PERMIT - 10F sides		/	7. UNIT AGREEMENT NAME	
OIL GAS GAS GAS	d otnes			
WELL WELL OTHER NAME OF OPERATOR			8. FARM OR LEASE NAME	
Robert L. Bayless			Jicarilla 462	
. ADDRESS OF OPERATOR		RECEIVED	#1	
P.O. Box 168, Farmington, NM 87499		/	10. FIELD AND POOL, OR WILDCAT	
See also space 17 below	oft location clearly and in accordance with any	JAN 1 5 1987	Wildcat	
At surface		3741 I 3 1301	11. SEC., T., R., M., OR BI	E. AND
1190	'FSL & 1081'FWL	UREAU OF LAND MANAGEMENT		
	_	FARMINGTON RESOURCE AREA	Sec. 22, T30N	
4. PERMIT NO.	15. ELEVATIONS (Show whether Di		12. COUNTY OR PARISE	
	7134' GL	7147' RKB	Rio Arriba	NM
ð.	Check Appropriate Box To Indicate N	Nature of Notice, Report, or C	ither Data	
NO	TICE OF INTENTION TO:		ENT REPORT OF:	
	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING W	BLL
TEST WATER SHUT-OFF FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	BING
SHOOT OR ACIDIZE	ABANDON®	SHOOTING OR ACIDIZING	MEMNOONMEN	
REPAIR WELL	CHANGE PLANS		cement prod. c	
(Other)	OMPLETED OPERATIONS (Clearly state all pertine)	Completion or Recompl	etion Report and Log for	B.)
			ANC 0 1987	
(This space for Federa APPROVED BY CONDITIONS OF APP	or State office use) TITLE PROVAL, IF ANY:	Operator	ACCEPTED I	14/87 FOR RECORD 6 1987
	*See Instruction	ns on Revérse Side	FARMINGIUN	RESOURCE AREA

ROBERT L. BAYLESS

PETROLEUM PLAZA BUILDING
P.O. BOX 168
FARMINGTON, NEW MEXICO 87499
(505) 326-2659

DAILY REPORT

Jicarilla 462 #1 1190' FSL & 1081' FWL Sec. 22, T30N, R3W Rio Arriba County, New Mexico

1/12/87 Reached T.D. at 2:00 p.m. 1/11/87. Circulate for 3/4 hour. Short trip. Circulate for logs 1 hour. TOH, rigged up Welex and ran IEL-DCL-FDL logs from loggers TD of 4145 ft. to surface. TIH with drillpipe. LDDP and collars and ran 4-1/2" casing as follows:

DESCRIPTION	LENGTH	DEPTH
KB to landing point	12.00	0-12
101 jt. 4-1/2" 11.6#/ft. J55 csg. (Korean DongJin) 1 DFFC	4060.18 2.25	12-4072 4072-4074
1 jt. 4-1/2" 11.6#/ft. J55 csg. (Korean DongJin) 1 cement filled guide shoe	40.30 1.00 4115.73	4074-4115 4115-4116

Centralizers @ 4095, 3750, 3670, 3629, 3589, and 3509.

Rigged up Dowell and cemented casing with 200 sacks (252 ft. ³), 50/50 pozmix 2% gel 10% salt 1/4# flocele/sack. Good circulation throughout job. Bumped plug to 1450 psi. Plug down at 6:45 a.m. 1/12/87. Set slips and ran rtemperature survey - top of cement at 2400 ft. RKB. Wait on completion.