

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. UNIT AGREEMENT NAME San Juan 30-6 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 30-6 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WELL NO. 426
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1460'S, 1450'W	10. FIELD AND POOL, OR WILDCAT Undes. Fruitland Coal
14. PERMIT NO.	11. SEC., T., R., M., OR ALK. AND SURVEY OR AREA Sec. 34, T-30-N, R-07-W N.M.P.M.
15. ELEVATIONS (Show whether OF, ET, OR, etc.) 6230' GL	12. COUNTY OR PARISH 13. STATE Rio Arriba NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Running Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Supply state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

07-08-88 TD 2940'. Ran 69 jts. 7", 20.0#, K-55 intermediate casing, 2927' set @ 2940'. Cemented with 430 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (825 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (112 cu.ft.). WOC 12 hours. Held 1200#/30 min. TC by TS @ 50'.

07-21-88 TD 3085'. Ran 5 jts. 5 1/2", 23.0#, P-110 casing liner, 210' set @ 3085'. Float shoe set @ 3085'. Top of liner hanger @ 2874'. Did not cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Regulatory Affairs

DATE

09-26-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side