UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Noti	ces and Reports on Wells		
1. Type of Well GAS	AUB 3 0 199	5. 6.	Lease Number SF-080714 If Indian, All. or Tribe Name Unit Agreement Name
2. Name of Operator BURLINGTON RESOURCES OIL	E GAS COMPANY OF THE DISTRESS	3	San Juan 30-6 Unit Well Name & Number
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	30-039-24275
4. Location of Well, Footage, Se 1670'FNL, 845'FEL, Sec.11, T	ec., T, R, M -30-N, R-6-W, NMPM		Field and Pool Basin Fruitland Coal County and State Rio Arriba Co, NM
Type of Submission _X_ Notice of Intent Subsequent Report Final Abandonment	Recompletion New Plugging Back Nor	ange of Pla w Construct n-Routine D ter Shut on nversion to ion	tion Fracturing ff
13. Describe Proposed or Comp It is intended to install procedure and wellbore di	a pump in the subject well a	according	RECEIVED RECEIVED 39 AUG -4 PM 1: 3
/ / / d	foregoing is true and corre	trator_Dat	e 8/2/99
APPROVED BY CONDITION OF APPROVAL, if any:	h— Title (sam dea,	·Date _	department or agency of

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

San Juan 30-6 #437 PUMPING UNIT INSTALLATION PROCEDURE 7/28/99

<u>Unit H, Section 11, T30N-R6W, Rio Arriba County, New Mexico</u> <u>Lat. 36.829742 / 36° 49.78'</u> <u>Long. 107.425522 / 107° 25.53'</u>

- 1. MIRU pulling unit.
- 2. NDWH / NU BOP. Kill if necessary with produced Fruitland coal water.
- 3. PU one joint of tubing and TIH to tag for fill.
- 4. TOOH, laying down 2-7/8" tubing (tubing is set @ 3010'. There are 102 joints of 2-7/8" 6.5# J-55 and an "F" nipple @ 3076').
- 5. PU 4-3/4" bit and 2-3/8", 4.7#, J-55 EUE tubing and TIH to COTD. Circulate hole clean. (Note: COTD is @ ~3119'.)
- 6. TIH w/ 2-3/8" tubing string configured for downhole pump and land @ 3114'. Purge valve will be on bottom, followed by pup joint, perforated sub, and seating nipple. Space out as needed with pup joints.
- 7. Hang tubing in donut. ND BOP / NUWH.
- 8. TIH w/ new 1.25" top hold down pump, 3/4" Grade D sucker rods w/ spray metal couplings, polished rod, and polished rod liner. (Note: Vendor contact is listed below)
- 9. Seat the downhole pump, hang horses head, and space out pump.
- 10. Load tubing, and pressure test.
- 11. Start pumping unit and test (adjust spacing as required).
- 12. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: D.W. Mussett

Pump vendor: ENERGY PUMP

Leo Noves (a) 564-2874

San Juan 30-6 Unit #437 July 28, 1999 Basin Fruitland Coal Unit H, Section 11, T30N, R6W, Rio Arriba County, New Mexico

