

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME San Juan 30-6 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME San Juan 30-6 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499		9. WELL NO. 459
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1490'S, 1188'W		10. FIELD AND POOL, OR WILDCAT Undes. Fruitland Coal
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-30-N, R-06-W N.M.P.M.
15. ELEVATIONS (Show whether OF, BT, OR, etc.) 6237' GL		12. COUNTY OR PARISH 13. STATE Rio Arriba NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PELL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

Spud Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. HAS RISE PROPOSED OR COMPLETED OPERATIONS. (If rise state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

09-05-88 Spudded well at 8:00 pm 09-05-88. Drilled to 225'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 225'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.). Circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

09-09-88 TD 2920'. Ran 68 jts. 7", 20.0#, K-55 intermediate casing, 2920' set @ 2933'. Cemented with 450 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (868 cu.ft.) followed by 100 sks. Class "B" with 1% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min.

RECEIVED  
SEP 11 1988  
OIL CON. DIST.

18. I hereby certify that the foregoing is true and correct

SIGNED Regina J. [Signature] TITLE Regulatory Affairs DATE 09-12-88

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side