IN I hereby certify that SIGNED Key in (This space for Fede APPROVED BY	the forestoing of pressand H. McCord rai or State office use)	V	etroleum Engineer	NOV1 51988 OIL CON. E DIST. 3	3
IN. I hereby certify that SIGNED	the forething of strained of the M. McCord	V	etroleum Engineer	NOV1 51988 OIL CON. E DIST. 3	3
RECEIVED RECEIVED ROL -9 AN IO: 07	FARMENTON, NEW MEXICO			NOV1 51988	3
				D EGEIV	Em
nen: 2 this work.	MULTIPLE ABANDON* CHANGE P R COMPLETED OPERATIONS (f well is directionally drill	Clearly state all pertinent led. give subsurface locati	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) Spud not (NOTE: Report resul	REPAIRING WEI ALTERING CASI: ABANDONMENT ICe; Surface casi: ts of multiple completion on nepletion Report and Log form. 18. including estimated date of ical depths for all markers as	ng X Well
16.		219 'GL 7231 ' te Box To Indicate N	ature of Notice. Report, or	Rio Arriba Other Data	NM
14. PERMIT NO.	1	EVATIONS (Show whether DF,		Section 30, T3	3. STATE
4. LOCATION OF WELL (See also space 17 be	168, Farmington, Report location clearly and low.) 25' FNL & 965' H	d in accordance with any	State requirements.*	2 10. FIELD AND POOL, OR V East Blanco 11. SEC., T., B., M., OR BLE SURVEY OR AREA	P.C.
Robert L. Bayless 3. ADDRESS OF OPERATOR				Jicarilla 464	
2. NAME OF OPERATOR				Jicarilla Apac 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	t e e e e e e e e e e e e e e e e e e e
OUL GAS WELL WELL	X OTHER			linemille Amer	- h - M 2 h
(Do not use thi	s form for proposals to dr Use "APPLICATION FO	AND REPORTS C	ON WELLS ack to a different reservoir. oposals.)	Jicarilla Cont 6. IF INDIAN, ALLOTTEE 0	

*See Instructions on Reverse Side

ROBERT L. BAYLESS

PETROLEUM PLAZA BUILDING
P. O. BOX 168
FARMINGTON, NEW MEXICO 87499
(505) 326-2659

JICARILLA 464 #3 Section 30, T30N, R3W 1525' FNL & 965' FEL Rio Arriba County, New Mexico

DAILY REPORT

11/05/88 Spud well at 4:45 PM on 11/4/88. Drilled 140' of 12 1/4" surface hole. Ran 3 jts. of 8 5/8" 24#/ft J-55 casing (123.30 ft.) and landed at 136' RKB. Rigged up Cementers. Inc. Cemented surface with 100 sx (118 ft³) of Class B cement with 2% CaCl2. Good circulation throughout job. Circulated cement to surface. Plug down at 10:30 PM on 11/4/88. Wait on cement.

30