

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-347-20

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name San Juan 30-6 Unit
2. Name of Operator Meridian Oil Inc.	8. Well No. 443
3. Address of Operator PO Box 4289, Farmington, NM 87499	9. Pool name or Wildcat Basin Fruitland Coal
4. Well Location Unit Letter <u>C</u> : <u>2200</u> Feet From The <u>North</u> Line and <u>1360</u> Feet From The <u>East</u> Line Section <u>36</u> Township <u>30N</u> Range <u>6W</u> NMPM <u>Rio Arriba</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6806' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

05-06-89 Spudded well at 11:15 am 05-06-89. Drilled to 246'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 246'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

05-09-89 TD 3524'. Ran 82 jts. 7", 20.0#, K-55 intermediate casing, 3512' set @ 3524'. Cemented with 600 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (1033 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.) circulated to surface. WOC 12 hours. Held 1200#/30 min.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Frank T. Chavez TITLE Regulatory Affairs DATE 5-9-89

TYPE OR PRINT NAME _____ TELEPHONE NO. _____

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE _____ DATE MAY 12 1989

CONDITIONS OF APPROVAL, IF ANY: