Ferm 3160-5 (November 1983) (Formerly 9-331)

16.

UNITED STATES DEPARTMENT OF THE INTERIOR VELLE BIDER

6257' GL

SUBMIT IN TRIPLICATES (Other instructions on re-

Bunger Durent no. 1004-Expires August 31, 1985 5. LEASE DESIGNATION AND BERIAL NO

Rio Arriba

SF 079060

ALIMENI	Oi.	HIE MILEMON WAS AND ADDRESS OF	
DIDEALI OF L	ΔND	MANAGEMENT	

BUREAU OF LAND MANAGEMENT	DI 073000
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT.—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME NEBU
OIL WELL WELL OTHER WELL WELL OTHER 2. NAME OF OPERATOR Blackwood & Nichols Co., Ltd. 3. ADDRESS OF OPERATOR P. O. Box 1237, Durango, CO 81302-1237 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 160' F/NL - 1555' F/EL	Agreement No. I, Sec. 929 8. FARM OR LEASE NAME Northeast Blanco Unit 9. WBLL NO. 429 10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal 11. SEC., I., E., M., OR BLE. AND SURVEY OR ARMA Sec. 17-30N-7W
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OF PARISH 13. STATE Rio Arriba New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
NOT	ICE OF D	NTENTION 10.	r	, , , , , , , , , , , , , , , , , , , ,	REPAIRING WELL	
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	ALTERING CASING	
PRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT		
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL		CHANGE PLANS	xx	(Other) (Norn: Report results of mult Completion or Recompletion Re	iple completion on Well	
(Other)		والمناسبين والمناز والمناز والمناز والمناز والمناز	i		a astimated date of starting	ſ

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to change APD approved December 13, 1988

Will drill 12 1/4" surface hole to a total depth of 300'. 9 5/8" surface casing will be run and cemented with cement returns to surface. WOC 12 hours. Test to 600 psig. Drill 7 7/8" hole with mud through the Pictured Cliffs Sandstone to 3450'. Run Gamma Ray, Density-Neutron, and Induction logs. Set 5 1/2" production string cemented back to surface.

DATE December 19, TITLE Operations Manager (This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

The 18 II S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the