

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

1. TYPE OF WELL GAS		5. LEASE NUMBER SF-080711A	
2. OPERATOR <i>Meridian</i> EL PASO NATURAL GAS CO.		6. IF INDIAN, ALL. OR TRIBE NAME	
3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499		7. UNIT AGREEMENT NAME SAN JUAN 30-6 UNIT	
4. LOCATION OF WELL 1560'S 1610'W		8. FARM OR LEASE NAME SAN JUAN 30-6 UNIT	
		9. WELL NO. 481	
		10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL	
		11. SEC. T. R. M OR BLK. SEC. 30 T30N R06W NMPM	
14. PERMIT NO.	15. ELEVATIONS 6828'GL	12. COUNTY RIO ARRIBA	13. STATE NM
16. NOTICE OF INTENTION TO: Change Plans			
17. Describe proposed or completed operations			

Attached is a revised operations plan, BOPE diagram and anticipated production facilities diagram on the subject well.

RECEIVED
APR 02 1990
OIL CON. DIV.
DIST. 3

18. AUTHORIZED BY: *[Signature]*
REGULATORY AFFAIRS

9/9/89
DATE

NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.

=====

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITION OF APPROVAL, IF ANY: _____

APPROVED
MAR 26 1990
DATE
FARMINGTON LAND AREA

Well Name: 481 SAN JUAN 30-6 UNIT 1560'S 1610'W
 Sec. 30 T30N R06W RIO ARRIBA NEW MEXICO
 BASIN FRUITLAND COAL Elevation 6828'CL

Formation tops: Surface- SAN JOSE
 Ojo Alamo- 2767
 Kirtland- 2967
 Fruitland- 3477
 Fruitland Coal Top- 3631
 Fruitland Coal Base- 3738
 Total Depth- 3739
 Pictured Cliffs- 3742

Logging Program: Mud logs from 3477 to total depth.

Mud Program:	Interval	Type	Weight	Visc.	Fl. Loss
	0 - 200	Spud	8.4 - 8.9	40-50	no control
	200 - 3739	Non-dispersed	8.4 - 9.5	30-60	no control

Casing Program:	Hole Size	Depth	Interval	Csg. Size	Weight	Grade
	12 1/4"	0 - 200		8 5/8"	24.0#	K-40
	7 7/8"	0 - 3739		5 1/2"	15.5#	K-55
		0 - 3739		2 3/8"	4.7#	J-55

Float Equipment: 8 5/8" surface casing - saw tooth guide shoe.

5 1/2" production casing - float shoe on bottom.

Three centralizers run every other joint above shoe.

Wellhead Equipment: 8 5/8" x 5 1/2" x 2 3/8" x 11" 3000 psi xmas tree assembly.

Cementing:

8 5/8" surface casing - cement with 140 sacks of class "B" cement with 1/4# floccule/sack and 3% calcium chloride (165 cu ft. of slurry, 100% excess to circulate to surface). WOC 12 hours. Test casing to 600 psi for 30 minutes.

5 1/2" production casing - lead with 113 sacks of 65/35 class "B" poz with 6% gel, 2% calcium chloride and 1/2 cu.ft. per-lite/sack (10.3 gallons of water/sack) tail with 100 sacks of class "B" with 2% calcium chloride. 337 cu ft. of slurry, 100% excess to cover the Ojo Alamo. Run temperature survey at 8 hours. WOC 12 hours. Test casing to 1500 psi for 30 minutes.

BOP and Tests:

Surface to TD - 11" 2000 psi (minimum) double gate BOP stack


From surface to TD - choke manifold (Reference Figure #3).

Pipe rams will be actuated at least once each day and blind rams actuated once each trip to test proper functioning. A Kelly cock valve and drill string safety valves to fit each drill string will be maintained and available on the rig floor.

Addition Information:


The Fruitland coal formation will be completed.
This gas is dedicated.
The W/2 of Section 30 is dedicated to this well.

FIGURE #1




Minimum POE Installation for a typical Fruitland Coal well from surface to Total Depth. 11", 2000 psi working pressure double gate NOT equipped with blind and pipe rams.

FIGURE #3



Minimum choke manifold configuration for a typical Fruitland Coal well from surface to TD. 2", 2000 psi working pressure equipment with two chokes.

LONG STRING FCCU BOP
UPDATING 9/6/11



MERIDIAN OIL

ANTICIPATED
PRODUCTION FACILITIES
FOR A
FRUITLAND WELL

J. Falconi

4/28/89