Form 3160-5 (November 1983) (Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO

NM 012299

BUREAÚ	OF	LAND	MANA	GEMENT

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS	ĔŨ
			deenen or niug			

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME ī. 90 JAN 12 AHII: 19 San Juan 31-6 Unit WELL 8. FARM OR LEASE NAME NAME OF OPERATOR San Juan 31-6 Unit Northwest Pipeline Corporation 9. WBLL NO. 3. ADDRESS OF OPERATOR #202 3539 East 30th Street - Farmington, NM LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal 11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA 1495' FSL & 1695' FWL NE/4 SW/4 Sec. 1N, T30N, R6W 12. COUNTY OR PARISH 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. New Mexico Rio Arriba 6438' GR

propries fox Mindicale Nature of Notice, Report, or Other Data 16. EB 07 1990 ER CASINO REPAIRING WELL WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT PRACTURE TREAT SHOOTING OR ACIDIZING SHOOT OR ACIDIZE Completion Operations (Other) REPAIR WELL (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

12-14-89: MOL & RU. NU BOPs. Tested blind rams to 2000# - ok.

Drilled shoe at 3121' & coals from 3145' to 3244' (total 22'). TD at 3244'. 12-15-89:

Blowing well w/ 1.8 MMCF/D air.

12-17-89: Blowing well w/ air 3.0 MMCF/D.

12-18 & 12-19-89: Blowing w/ 3.6 MMCF/D air.

12-20-89: Blew well clean & TOH w/ drill pipe. Ran 5 jts (225') of 5-1/2", 23#, P110, USS smls w/ TIW (JGS) liner hanger. Set from 3018' to 3243' (7" shoe at 3121', TD at 3244'). PBTD at 3241'. Ran GR/CCL and perfed from 3142'-3172', 3180'3210', 3233'-3241'. 272 total holes (.74" dia.). Tallied 2-7/8" & began TIH.

12-21-89: Finished TIH w/ 2-7/8" tbg. Tagged PBTD at 3241', no fill. Pulled up and landed tbg. Ran 102 jts (3203') 2-7/8", 6.4#, J-55, 10rd NUE Argentina. Tbg landed at 3226' KB. SN at 3193' KB. Perfs 3142' to 3241'. ND BOP's, NU wellhead. Pump plug. Rig down. Unable Unable to gauge.

18. I hereby certify that the foregoing is true and correct SIGNED		Durduction Assistant	1-11-90	
SIGNED Cappio Harmon	TITLE	Production Assistant	DATE /-//	
(This space for Federal or State office use)		ACCE	PIED FOR RECORD	-
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	F	DATE	·
	₹,	84.757	1000	

*See Instructions on Reverse Side

Rilling

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.