UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS 1. TYPE OF WELL GAS 2. OPERATOR EL-PASC-NAMPURAL GAS-CO. 3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499 4. LOCATION OF WELL 790'S 845'W 10. FIELD, POOL, OR WILDCAT BASIN 11. SEC. T. R. M OR BELK SEC. 9 T30N ROGW NMPM 12. COUNTY 13. STATE 16. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3t calcium chloride, 189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120889 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement with 24 cement with 380 sacks of Class G cement with 24 cement with 380 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 28 call (115 cu ft.). Tail with 100 sacks of Class G cement with 38 sacks of Class G		BUREAU OF LAND	MANAGEMENT	7. 		
1. TYPE OF WELL GAS 2. OPERATOR EL-PRO-MATURAL GAS CO. 3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499 4. LOCATION OF WELL 790'S 845'W 14. PERMIT NO. 15. ELEVATIONS 30-039- 16. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations TD 225' Ran 5 jts of 9 5/8" 40.0 # N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 12089 TD 2957', Ran 72 jts of 7" 23.0 # K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 67,35 POZ, 6% gel, 2% Cacl2, 5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% Cacl2 (115-cu ft) Circulated 20 bbl to surface. NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD		SUNDRY NOTICES AND F	EPORTS ON WELL	S		
3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499 4. LOCATION OF WELL 790'S 845'W 10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 9 T30N RO6W NMPM 14. PERMIT NO. 15. ELEVATIONS 6275'GL 17. Describe proposed or completed operations 17. Describe proposed or completed operations 18. FARM OR LEASE NAME SAN JUAN 30-6 UNIT 9. WELL NO. 405 10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 9 T30N RO6W NMPM 17. DESCRIBE PROPOSED 18. SUBSEQUENT REPORT OF: SPUD 19. COUNTY RIO ARRIBA 10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 9 T30N RO6W NMPM 12. COUNTY RIO ARRIBA 13. STATE RIO ARRIBA 14. PERMIT NO. 15. ELEVATIONS 6275'GL 16. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations FEB 07 1990 CIL CON. DIV. DIST. 3 TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement with 2% CaCl2 (115 cu ft.) Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS ACCEPTED FOR RECURU APPROVED BY TITLE PATK 05 1990			NM-0	NM-03384		
P O BOX 4289 FARMINGTON, NM 87499 4. LOCATION OF WELL 790'S 845'W 10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 9 T30N ROGW NMPM 14. PERMIT NO. 15. ELEVATIONS 30-039- 6275'GL 16. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations FEB 07 1990 OIL CON. DIV. DIST. 3 TD 225' Ran 5 jts of 9 5/8" 40.0 % N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4 % Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0 % K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 POZ, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.) Circulated 20 bbl to surface. 18. AUTHORIZED BY: NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. APPROVED BY TITLE PATK 05 1990 ACCEPTED FOR RECORD			1	4		
### BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 9 T30N R06W NMPM 14. PERMIT NO. 15. ELEVATIONS 30-039- 6275'GL 12. COUNTY RIO ARRIBA NM MID 13. STATE RIO ARRIBA NM MID 15. ELEVATIONS 12. COUNTY RIO ARRIBA NM MID 15. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations FEB 07 1990 17. Describe proposed or completed operations FEB 07 1990 SPUD DATE: 120689 SPUD TIME: 1700 DIST. 3 TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.) Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS DATE NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE DATE	P O BOX 4289		SAN 9. WELL NO	SAN JUAN 30-6 UNIT 9. WELL NO.		
30-039- 6275'GL RIO ARRIBA NM 16. SUBSEQUENT REPORT OF: SPUD 17. Describe proposed or completed operations SPUD DATE: 120689 SPUD TIME: 1700 Cli CON. DIV. DIST. 3 TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS DATE NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD			BASI	BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK.		
17. Describe proposed or completed operations PEB 07 1990 OIL CON. DIV. DIST. 3 TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.) Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS DATE NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD				RRIBA NM	3	
SPUD DATE: 120689 SPUD TIME: 1700 TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS DATE NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD	16. SUBSEQUENT REPO	ORT OF: SPUD		IN EUGHVE		
TD 225' Ran 5 jts of 9 5/8" 40.0# N-80 casing, 211' set @ 224' Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE PATE 0.5 1990	17. Describe propose	ed or completed oper	ations	FEB 07 1990		
Cemented with 160 sacks of Class G cement with 1/4# Flocele/sack and 3% calcium chloride, (189 cu ft.). Circulated 14 bbl to surface. WOC 12 hours. Pressure tested to 600 psi for 30 minutes. Held OK. DATE: 120989 TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS DATE NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE PATE 05 1990	SPUD DATE: 120	689 SPUD TIME:	. 70 0			
TD 2957', Ran 72 jts of 7" 23.0# K-55 casing, 2944' set @ 2957' Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE PATE 05 1990	Cemented Flocele/sa Circulate	with 160 sacks of Cl ack and 3% calcium o d 14 bbl to surface.	lass G cement w chloride,(189 . WOC 12 hours	vith 1/4# cu ft.). s.	٠.	
Lead with 380 sacks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, .5 cu ft perlite (764 cu ft.). Tail with 100 sacks of Class G cement with 2% CaCl2 (115 cu ft.). Circulated 20 bbl to surface. 18. AUTHORIZED BY: REGULATORY AFFAIRS NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE PATE 05 1990	DATE: 120	989				
NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5. (This space for Federal or State office use) ACCEPTED FOR RECURD APPROVED BY TITLE PATE 05 1990	Lead with Poz, 6% go Tail with	380 sacks of Class el, 2% CaCl2, .5 cu 100 sacks of Class	G cement 65/35 ft perlite (7 G cement with	764 cu ft.).	7'	
(This space for Federal or State office use) ACCEPTED FOR RECORD APPROVED BY TITLE PATE 05 1990			Lilled SS	/2-/3-89 DATE		
(This space for Federal or State office use) ACCEPTED FOR RECORD APPROVED BY TITLE PATE 05 1990						
				ACCEPTED FOR RECURL	}	
CONDITION OF ADDROVAL TO ANY.			LE	PATE 0 5 1990		
CONDITION OF APPROVAL, IF ANY: FARMING FOR EXCENT LIKEA BY 2.1.1. BY 2.1.1. FARMING FOR EXCENT LIKEA	CONDITION OF APPROV	nu, ir Ani:	シ (ケた)	FARMINGPOST AZERG GLE SEA		