Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals	SF-078997
	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well	San Juan 30-5 Unit
Oil Gas Well Other	8. Well Name and No. 204
2. Name of Operator PHILLIPS PETROLEUM COMPANY	9. API Well No.
3. Address and Telephone No.	30-039-24685
300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool, or Exploratory Area Basin Fruitland Coal
	11. County or Parish, State
Unit G 1967' FNL & 1416' FEL S 7, T30N, R5W	Rio Arriba, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT	
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent  Abandonment  Recompletion	Change of Plans
	New Construction
Subsequent Report 1000 Plugging Back	Non-Routine Fracturing
Final Abandonment Notice Casing Repair  Altering Casing	Water Shut-Off Conversion to Injection
DIV. Klother As Per NTL-FRA-90-1	Dispose Water
	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	my proposed work. If well is directionally drilled,
Description of cement job to fulfill requirements for protection of us	sable water zones including
the Ojo Alamo Formation, as per NTL-FRA-90-1.	
Date: 8/10/90 Time Started: 2212 Time Comp	oleted: 2339
Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing S	
Turbo Centralizers at 2533 , 2488 , 2444 .	
Spring Type Centralizers at 2945 , 2881 , 2794 , 2704	<u></u>
Mud Flush 10 BBls, Spacer 10 Fresh Water.	
Lead Slurry 500 sx Standard 65/35 POZ, 12% Gel, 1/4#/sx Flocele, 11.7	ppg @ 2.30 ft <sup>3</sup> /sx yield.
Mid Slurry 100 sx Standard, 1/4#/sx Flocele, 15.6 ppg @ 1.18 ft <sup>3</sup> /sx	yield.
Tail Slurry 50 sx Standard, .75% CFR-3, 17.5 ppg @ .94 ft <sup>3</sup> /sx yield.	
Displaced Plug with 113 Bbls Fresh Water.	
Volume Cement Circulated 64 Bbls/Saccks	
Average Pressure 662 PSI, Average Rate 7 BPM, Bumped Plu	ng with 1200 PSI.
14. I hereby certify that the foregoing is true and correct  R. A. Allred  Title Drilling Supervisor	9-14-90
Signed	
•	PTED FOR RECORD

SEP 26 1990 Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON RESOURCE AREA