Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Serial No. SF-078997 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE <u>San Juan 30-5 Unit</u> Type of Well X Gas 8. Well Name and No. Oil 2. Name of Operator SJ 30-5 Unit #204 Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-039-24685 5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit G. 1967' FNL & 1416' FEL Basin Fruitland Coal 11. County or Parish, State Sec. 7, T30N, R5W NM Rio Arriba, CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment Recompletion **New Construction** X Subsequent Report Non-Routine Fracturing Plugging Back Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 2/3/98 LO/TO location. RU B&R & set slickline in "F" nipple. MIRU Big A #22. NU BOPs and test. Circ. hole w/air and cleanout to PBTD. Set plug in "F" nipple. COOH w/production tubing. RIH w/stator and tubing. BHA consists of bull plug, 6' perf sub, expendable chedk. 1.43" "F" nipple, Beau Tech stator, 1 jt 2-7/8" and 95 its of 2-3/8" tubing. Landed 2" off bottom @ 3087... ND BOP, NU WH. PU & run BMW 60-4100 rotor. 2' pony rods, 121 7/8" rods, 4' & 6' pony rods, 22' 1-1/4" polish rod. Landed rotor in High-Nitril-High Speed stator. Installed drive head, pumped off chedk. started pump. Released rig. RD & MQ. OIL COM. DIV 14. I hereby certify that the foregoing is true and correct Regulatory Assistant 2-11-98 Title (This space for Federal or State office use) Title Approved by _ Conditions of approval, if any: FEB 1 7 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements