

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME San Juan 30-5 Unit	
2. NAME OF OPERATOR PHILLIPS PETROLEUM COMPANY		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR 300 W. Arrington, Suite 200, Farmington, N.M. 87401		9. WELL NO. 211	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit B, 1083' FNL & 1821' FEL		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal	
14. PERMIT NO. 30-039-24720		11. SEC., T., R., N., OR BLK. AND SUBST. OR AREA Sec. 31, T30N, R5W	
15. ELEVATIONS (Show whether DP, RT, GR, etc.) 6908'		12. COUNTY OR PARISH Rio Arriba	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Casing, Liner, Tbg.

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-09-90 - Aztec #301 - RU casing crew. Ran 7", 23#, J-55, LT&C set at 3531'. WOC 6.5 hrs. RU Western & cement with 500 SX 65/35 POZ cement with 12% gel and 1/4# gelflake per sk followed by 100 SX Cl 'B' cement with 1/4# gelflake per sk. Circ 45 SX cement. Plug down at 8:30 A.M. 6-11-90. Bumped plug with 2000 psi. Held. ND BOP Set casing slips with 75,000# RD & Release rig.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. A. Alfred
R. A. Alfred

TITLE Drilling Supervisor

DATE 8-27-90

(505) 599-3403

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

SEP 06 1990

FARMINGTON RESOURCE AREA

BY

MT

*See Instructions on Reverse Side