Form 3160-5 (June 1990)

(This space for Federal or State office use)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED					
Budget Bur	CAU	No.	10	34-0	135
Expires:	M	arch	31.	1993	

5. Lease Designation and Serial No.

NM-012335 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 30-5 Unit 1. Type of Well Oil Gas Well 8. Well Name and No. 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-039-24721 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State Unit N, 1061' FSL & 1540' FWL Jec 31, 301, 50 Rio Arriba CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Started: ____1930 Time Completed: 2045 Casing Size 7" 23# J-55 New Casing Seat Hole Size 8-3/4" Turbo Centralizers at 2833 , 2796 , 2751 . Spring Type Centralizers at 3275, 3209, 3125, 3043, 2963. Mud Flush 10 BBls, Spacer 10 Fresh Water. Lead Slurry 500 sx 65/35 Cl "B" Ideal, 12% Gel, 1/4#/sx Flocele, 11.7 ppg @ 2.3 ft vield. Mid Slurry --Tail Slurry 150 sx Std. Cl "B" Ideal, 1/4#/sx Flocele, 15.6 ppg @ 1.18 ft 3/yield. Displaced Plug with 127 Bbls Fresh Water. Volume Cement Circulated 80 Bbls/Backs
Average Pressure 380 PSI, Average Rate 7.8 BPM, Bumped Plug with 1500 PSI. 14. I hereby certify that the foregoing is true and correct R. A. Allred

– იბт -0 4-1990

FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any faile, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title Drilling Supervisor