

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24768
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-347-39
7. Lease Name or Unit Agreement Name San Juan 30-5 Unit
8. Well No. 219
9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6344' GL

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator PHILLIPS PETROLEUM COMPANY
3. Address of Operator 300 W. ARRINGTON, SUITE 200, FARMINGTON, NM 87401
4. Well Location Unit Letter L : 1586 Feet From The South Line and 1304 Feet From The West Line Section 16 Township 30N Range 5W NMPM Rio Arriba County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, 9-5/8" Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-17-90

MIRU Aztec Well Service Rig No. 301. Spudded 12-1/4" hole @ 10:00 PM. Ran 9-5/8" , 36#, K-55, ST&C casing set at 287.68'. Ran 9-5/8", 36#, K-55, ST&C casing set @ 287.68' RU Howco and cemented w/250 Sx C1 "B" cement. Circ. 95 Sx cement. Plugged down @ 10:30 AM on 10-18-90. Bumped plug w/800 psi. WOC 10 hours. NU BOP and pressure tested to 1000 psi - okay.

RECEIVED  
OCT 23 1990  
OIL CON. DIV.  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. A. Allred TITLE Drilling Supervisor DATE 10-19-90  
TYPE OR PRINT NAME R. A. Allred TELEPHONE NO.

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE OCT 23 1990  
CONDITIONS OF APPROVAL, IF ANY: