Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 11, 1003

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-080066 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Pr 5:20 Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 30-5 Unit 1. Type of Well 8. Well Name and No. Oil Gas Other 213 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 30-039-24826 3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, № 87401 505/599-3400 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit B, 995! FNL & 1480' FEL Rio Arriba, NM Sec. 5, T30N, R5W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Plugging Back Non-Routine Fracturing \_\_ Subsequent Report Water Shut-Off Conversion to Injection Final Abandonment Notice Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. \_\_\_ Time Completed: 0500 \_\_ Time Started: 0346 8-28-90 Casing Size 7" 23# J-55 New Casing Seat 3163 , 2677 <u>, 2719</u> Turbo Centralizers at 2763 Spring Type Centralizers at 3140 \_\_\_\_, <del>30</del>70 Mud Flush 10 BBls, Spacer 10 Fresh Water. Lead Slurry 500 SX 65/35 POZ, 12% Gel, 1/4 / SK Celloflake, 11.7 ppg @ 2.3 ft 3 / SX yield Mid Slurry 100 SX C1"B", 14/SK Flocele, 15.6 ppg @ 1.18 ft 2/SX yield Tail Slurry 50 SX C1"B", .75%. CFR-3, 17.2 ppg @ .97 ft 3/SK yield. Displaced Plug with 121 Bbls Fresh Water. BXXbs/Sacks 98 Volume Cement Circulated \_ PSI, Average Rate 6 BPM, Bumped Plug with 700 PSI. Average Pressure \_250\_\_\_ R. A. Allred 14. I hereby certify that the foregoing Tite Drilling Supervisor (This space for Federal or State office use ACCEPTED FOR RECORD OCT 03 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Space of t