

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. SF-078740	
2. NAME OF OPERATOR PHILLIPS PETROLEUM COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 300 W. Arrington, Suite 200, Farmington, NM 87401		7. UNIT AGREEMENT NAME San Juan 30-5 Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit M, 1086' FSL & 1015' FWL		8. FARM OR LEASE NAME	
14. PERMIT NO. 30-039-24828		9. WELL NO. 216	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6275'		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal	
		11. SEC., T., R., M., OR BLK. AND SUBV. OR AREA Sec. 20, T20N, R5W	
		12. COUNTY OR PARISH Rio Arriba	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-21-90 - MIRU Aztec Well Service Rig No. 301. Spudded 12 1/4" hole at 12:30 P.M. Ran 9 5/8", 36#, K-55, ST&C casing set at 285'. RU Howco and cement with 250 SX Cl 'B' with 3% CaCl₂ and 1/4# floccul/sk. Circ 90 SX cement. Plug down at 9:45 P.M. Bumped plug with 800 psi. Float held. WOC 8.5 hrs. NU BOP and test to 1000 psi - Okay.

RECEIVED

SEP 11 1990

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

R.A. Allred

TITLE

Drilling Supervisor

DATE

8-27-90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

SEP 04 1990

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY