

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department.

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24892
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 30-5 Unit
8. Well No. 227
9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6481' Unprepared

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator PHILLIPS PETROLEUM COMPANY
3. Address of Operator 300 W. ARRINGTON, SUITE 200, FARMINGTON, NM 87401
4. Well Location Unit Letter <u>A</u> : <u>988</u> Feet From The <u>North</u> Line and <u>1212</u> Feet From The <u>East</u> Line Section <u>28</u> Township <u>30N</u> Range <u>5W</u> NMPM Rio Arriba County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
12-18-90

MIRU Four Corners Rig No. 5. Spudded 12-1/4" hole @ 3:15 PM. Ran 9-5/8", 36#, J-55, ST&C casing set @ 283'. RU Western Co. and cemented w/250 Sx Class B cement w/3% CaCl<sub>2</sub> and 1/4# Flocele/Sk. Circ. 88 Sx cement. Plugged down @ 1:45 AM on 12-20-90. Bumped plug w/500 psi. WOC 10.5 hours. NU BOP and pressure tested to 1000 psi - okay.

RECEIVED  
DEC 24 1990  
OIL CON. DIV  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
SIGNATURE Frank T. Chavez TITLE Drilling Supervisor DATE 12-21-90  
TYPE OR PRINT NAME R. A. Allred TELEPHONE NO. \_\_\_\_\_

(This space for State Use)  
APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # DATE Dec 26 1990  
CONDITIONS OF APPROVAL, IF ANY: