*(December 1989)	Dens numerium		·
	DEPARTMENT (	F THE INTERIOR	Expires: September 30, 1990
		OF LAND MANAGEMENT	5 Lagge Papier Air & a. i. I. II
SUNDRY NOTICES A		ND REPORTS ON WELLS	5. Lease Designation & Serial #
Do not use this form for proposals to drill, deepen or		deepen or reentry to a different reserv	SF079060
	Use "APPLICATION FOR P	ERMIT-" for such proposals	The Manie
	SIIRMTT TN	TRIPLICATE	7. If Unit or CA, Agmt. Design.:
			Northeast Blanco Unit
1. Type of Well:	oil well	pas well X other	8. Well Name and No.:
			N.E.B.U.# 413R 9. API Well No.:
2. Name of Operator	: Blackwood & Nic	chols Co., Ltd.	7. API WELL NO.:
			30-039-24946 10. Field & Pool/Expltry Area:
3. Address of Operator: P.O. Box 1237, Durango, CO 81302-1237			io. Fletu & Poot/Expitry Area:
			Basin Fruitland Coal 11. County or Parish, State:
4. Location of Well: (Footage, Sec., T., R., M., or Survey Description)			
350' FNL, 460' FEL Section 20, T30N, R7W			Rio Arriba, New Mexico
12.	CHECK APPROPRIATE BO	DX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE	OF SUBMISSION	TYPE O	FACTION
		Abandonment	
Notice o	f Intent		Change of Plans
VV Subsemient Bereit		Recompletion	_XX_ New Construction
_XX_ Subsequent Report		Plugging Back	Non-Routine Fracturing
Final Abandonment Notice		Casing Repair	Water Shut-Off
		Altering Casing	Conversion to Injection
		Other:   (Note: Report results	of multiple completion on Well Completion
		or Recompletion Report	and log form )
		(Clearly state all pertinent details and	and Log form.)
vertical depths  10-02-90 Sr Run 7 jts (2 collar on boo ahead, ceme celloflake. surface. Pl 10-03-90 We BOPs, test h	for all markers and zone  oud 12-1/4" surf  296.65') 9-5/8"  ottom; one cent:  nt with 250 sx  Good circula  lug down at 3:45  eld on bradenhea  olind rams, casi	(Clearly state all pertinent details, and well is directionally drilled, give substitute and the second point of the second po	give pertinent dates, including estimated obsurface locations and measured and true  .0-01-90. Drill to 315'. , set at 313.35'; notched jt. Pump 20 Bbls water 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up
vertical depths  10-02-90 Sp Run 7 jts (2 collar on booth bo	for all markers and zone  oud 12-1/4" surf  296.65') 9-5/8"  ottom; one cent:  nt with 250 sx  Good circula  lug down at 3:45  eld on bradenhea  olind rams, casi	(Clearly state all pertinent details, and well is directionally drilled, give substitute at 6:00 p.m., 1 ace hole at 6:00	give pertinent dates, including estimated obsurface locations and measured and true  .0-01-90. Drill to 315'. , set at 313.35'; notched jt. Pump 20 Bbls water 1 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up
vertical depths  10-02-90 Sp Run 7 jts (2 collar on booth bo	for all markers and zone  pud 12-1/4" surf  296.65') 9-5/8"  ottom; one cent;  nt with 250 sx  Good circula  lug down at 3:45  eld on bradenhea  olind rams, casi  20'. Test pipe r	(Clearly state all pertinent details, and well is directionally drilled, give substitute at 6:00 p.m., 1 ace hole at 6:00	give pertinent dates, including estimated obsurface locations and measured and true  .0-01-90. Drill to 315'. , set at 313.35'; notched jt. Pump 20 Bbls water 1 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up
vertical depths  10-02-90 Sr Run 7 jts (2 collar on both ahead, ceme celloflake. surface. Pl 10-03-90 We BOPs, test k cement at 22 Continued or	for all markers and zone  pud 12-1/4" surf 296.65') 9-5/8"  pttom; one cent: nt with 250 sx  Good circula lug down at 3:45 eld on bradenhea olind rams, casi 20'. Test pipe r	(Clearly state all pertinent details, and well is directionally drilled, give substituted by the second of the sec	give pertinent dates, including estimated obsurface locations and measured and true  .0-01-90. Drill to 315'. , set at 313.35'; notched jt. Pump 20 Bbls water 1 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up
vertical depths  10-02-90 Sr Run 7 jts (2 collar on both ahead, ceme celloflake. surface. Pl 10-03-90 We BOPs, test k cement at 22 Continued or	for all markers and zone  pud 12-1/4" surf  296.65') 9-5/8"  pttom; one cent;  nt with 250 sx  Good circula  lug down at 3:45  eld on bradenhea  olind rams, casi  20'. Test pipe r  n attached page	(Clearly state all pertinent details, and well is directionally drilled, give substituted by the second of the sec	give pertinent dates, including estimated obsurface locations and measured and true  .0-01-90. Drill to 315'. , set at 313.35'; notched jt. Pump 20 Bbls water 1 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up
vertical depths  10-02-90 Sp Run 7 jts (2 collar on both ahead, ceme celloflake. surface. P] 10-03-90 We BOPs, test becement at 22 Continued or	for all markers and zone  pud 12-1/4" surf 296.65') 9-5/8"  pttom; one cent: nt with 250 sx  Good circula lug down at 3:45 eld on bradenhea olind rams, casi 20'. Test pipe r	(Clearly state all pertinent details, and well is directionally drilled, give substituted by the second of the sec	give pertinent dates, including estimated burface locations and measured and true  1.0-01-90. Drill to 315'.  1. set at 313.35'; notched jt. Pump 20 Bbls water  1. 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up psi, held OK. TIH, tag  1. Drill 8-3/4" hole.
vertical depths  10-02-90 Sr Run 7 jts (2 collar on both ahead, ceme celloflake. surface. Pl 10-03-90 We BOPs, test k cement at 22 Continued or  14. I hereby certify Signed: RW.	for all markers and zone  pud 12-1/4" surf  296.65') 9-5/8"  pttom; one cent;  nt with 250 sx  Good circula  lug down at 3:45  eld on bradenhea  olind rams, casi  20'. Test pipe r  n attached page	(Clearly state all pertinent details, and well is directionally drilled, give substituted by the substitute of the subst	give pertinent dates, including estimated burface locations and measured and true  10-01-90. Drill to 315'.  10-01-90. Dri
vertical depths  10-02-90 Sp Run 7 jts (2 collar on both ahead, ceme celloflake. surface. Pl 10-03-90 We BOPs, test becament at 22 Continued or  14. I hereby certify Signed: RW.  (This	for all markers and zone  pud 12-1/4" suri 296.65') 9-5/8"  ottom; one cent: nt with 250 sx  Good circula lug down at 3:45 eld on bradenhea olind rams, casi 20'. Test pipe r  n attached page	(Clearly state all pertinent details, and well is directionally drilled, give substituted by the substitute of substitute of the substitut	give pertinent dates, including estimated burface locations and measured and true  1.0-01-90. Drill to 315'.  1. set at 313.35'; notched jt. Pump 20 Bbls water  1. 2% CaCl <sub>2</sub> and 1/4 #/sk ulate 7 Bbls cement to psi, held OK. Nipple up psi, held OK. TIH, tag  1. Drill 8-3/4" hole.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency or the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

----