

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Hwy 64 NBU 3004, Farmington, NM 87401 (505) 599-3412

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit L, 2001' FSL & 1044' FWL  
Section 34, T30N, R5W

5. Lease Designation and Serial No.

NM-012332

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

242

9. API Well No.

30-039-25166

10. Field and Pool, or Exploratory Area  
Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud & 7" Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-1-92

MIRU Four Corners Rig #6. Spud 12-1/4" hole @ 1830 hrs on 10/1/92. Ran 9-5/8", 36# casing and set @ 281' RKB. Cemented w/200 Sx Class B w/3% CaCl<sub>2</sub> and 1/4# Sk Flocele. Circulated 20 Bbls cement. WOC 6 hrs. NU BOP's and tested to 1500 psi - okay.

10-8-92

Four Corners #6 ran 7", 23# casing and set @ 3510'. Cemented w/425 Sx 65/35 Poz w/12% gel and 1/4# Sk Flocele and 150 Sx Class B cement with 1/4# Sk Flocele. Circulated 110 Sx cement. Bumped plug w/1950 psi - okay. ND BOP and set slips w/60,000#. RD and released rig @ 1630 hrs on 10-8-92.

RECEIVED  
OCT 19 1992  
OIL CON. DIV.  
DIST. 3

RECEIVED  
BLM  
OCT 14 PM 3:08  
FARMINGTON, N.M.

14. I hereby certify that the foregoing is true and correct

Signed

Title Drilling Supervisor

Date 10-12-92

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOCD

FARMINGTON RESOURCE AREA  
SM