

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Hwy 64 NBU 3004, Farmington, NM 87401 (505) 599-3412

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit M, 1053' FSL & 1015' FWL  
Section 22, T30N, R5W

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-078739

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

234

9. API Well No.

30-039-25171

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other As Per NTL-FRA-90-1  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 8-23-92 Time Started: 1145 Time Completed: 1315  
Hole Size 8-3/4" Casing Size 7" Casing Seat 3050 Ft.  
Turbo Centralizers at 2715, 2629, 2499  
Spring Type Centralizers at 2068, 1725, 1168, 656, 30  
Mud Flush Bbls, Spacer Fresh Water.

Lead Slurry 400 Sx 65/35 Poz, 1/4#/sk Cellophane flakes: 12% Gel @ 11.8 ppG

Mid Slurry

Tail Slurry 150 Sx C1 G 1/4#/sk Cellophane flakes: 2% CaCl2 @ 15.8 ppG

Displaced Plug with 120 Bbls Fresh Water.

Volume Cement Circulated 65 Bbls/sacks

Average Pressure 300 PSI, Average Rate 5.5 BPM, Bumped Plug with 1300 PSI.

14. I hereby certify that the foregoing is true and correct

Signed R. A. Alfred  
(This space for Federal or State office use)

Title Drilling Supervisor

Date 9-2-92

Approved by  
Conditions of approval, if any:

Title

Date

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOCD

FARMINGTON RESOURCE AREA  
SEP 11 1992