Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED				
Budget Bun	eau No.	1004-0135		
Expires:	March	31, 1993		

5. Lease Designation and Serial No.

20	020	2520	<i>t</i> .

SUNDRY NOTICES AND REPORTS ON WELLS 6/ If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals [1] [1] 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well San Juan 31-6 Unit Oil Gas Well Other 8. Well Name and No. 38E 2. Name of Operator 9. API Well No. Phillips Petroleum Company 30-039-25204 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 5525 Hwy. 64, NBU 3004, Farmington, NM 87401 (505) 599-3454 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Dakota 11. County or Parish, State Unit B, 848' FNL & 1843' FEL Section 2, T-30-N, R-6-WRio Arriba, N.M. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans **New Construction** Recompletion Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Altering Casing
Other As Per NTL-FRA-90-1 Final Abandonment Notice Conversion to Injection \_\_ Dispose Water (Note: Report results of my Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Despription of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Started: 1400 hrs. Date: 10-04-93 Time Completed: 8-3/4" Casing Size 7" 23#/ft J-55 New; Casing Seat 3852 Turbo Centralizers at 3840', 3798', 3630', 3378', 3210', 3084', 2916' 2798',2585 None, Spring Type Centralizers None,
Mud Flush 10 Bbls, Spacer 10 Fresh Water. Stage 1: Lead Slurry 600 sxs 65:35 POZ + 12% gel + 1/4 / sk Celeflake @ 12.0 ppg Mid Slurry Tail Slurry 150 sxs C1 "B" + 2% CaCl, + 1/sk celeflake @ 15.6 ppg Stage 2: Lead Slurry None Mid Slurry Tail Slurry Volume Cement Circulated 70 Bbls/secks Displaced Plug with 123 Bbls Fresh Water. Average Pressure 1200 PSI, Average Rate 6.0 BPM, Bump Plug with 500 14. I hereby certify that the foregoing is true and correct 10-20-93 E. Robinson Title Sr. D&P Engineering (This space for Federal or State office use) SELECTION RECORD

\*See Instruction on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NIMOCYO

FARMINGTON DISTRICT 1