Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED			
Budget Bur	eau No.	1004-0135	
 Expires:	March	31, 1993	

	Expires:	MARCI	31,	נעמ	
Leuse	Designat	ion and	Sen	al N	0

	SUNDRY NOTICES AND REPORTS ON WELLS	**
o not use this	form for proposals to drill or to deepen or reentry to a different i	reservoir.
	HAR HADDIICATION COD DEDMIT HIME THE	

Do not use this form for proposals to d Use "APPLICATION FO	rill or to deepen or reentry to a different reservoir. OR PERMIT—" for such proposals	or justices of Title Name
SUBMI	T IN TRIPLICATE	€ If Unit or CA, Agreement Designation
1. Type of Well	1970;	San Juan 30-5 Unit
Other Gas Cother		8-/Well Name and No.
2. Name of Operator		SJ 30-5 Unit #76M
Phillips Petroleum Compa	iny	9 4PI Well No.
3 Address and Telephone No. 5525 Hwy. 64, NBU 3004,	Farmington, NM 87401 599-3454	30-039-255.11 10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T., R., M., or Survey D	Description)	-Basin Dakota &
Unit F, 1614' FNL & 1655 Section 15, T-30-N, R-5-		Rio Arriba, NM
CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Casing Repair	
Pinal Abandonment Notice	☐ Altering Casing ☐ Other Spud	Conversion to Injection
	La Utner Dp dd	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)
Describe Proposed or Completed Operations (Clearly state algive subsurface locations and measured and true vertice)	l pertinent details, and give pertinent dates, including estimated date of starting all depths for all markers and zones pertinent to this work.)*	any proposed work of well is directionally drilled.
5-31-95		
Ran 10-3/4" 45.5# K-55 I 450 sx Class G & 1/4#/sk ppg, 3.5 to 40 bpm @ 160	1 14-3/4" hole @ 0330 on 5/31/95 T&C surface casing and set at 3 3 cellophane 2/3% CaCl, w/1.15 y 0# - 180# psi. Circ. 195 sx bac Left 30 ft cement inside 10-3	60'. Mixed and pumped ield pumped @ 15.8 k to surface. Wood

4 hours. NU WH & BOP's. Test - Good test.

ACCEPTED FOR RECORD

JUN 09 1995

OUL COM. DAY.

FARMINGTON DISTRICT OFFICE

		RY Tall	
14. I hereby certify that the foregoing is true and correct Signed	у ты <u>Envir./Re</u> gul	latory Engineer Date	6-6-95
(This space for Federal or State office use)			
Approved by	Title	MPPHC AS AME	
Fitle 18 U.S.C. Section 1001, makes it a crime for any person knowing or representations as to any matter within its jurisdiction.	igly and willfully to make to any depa-	rtment or agency of the United States and false	e, fictitious or fraudulent statements
	*See Instruction on Dougle	e Side	1900