30-039-25670

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator Bl	JRLINGTON RESOURC	ES OIL & GAS CO.	Lease SAN JUAN 30)-6 UNIT	Well No. 17A			
Location of Well:	Unit E Sect NAME OF	18 Twp. 030N RESERVOIR OR POOL	Rge. 006W TYPE OF PROD. (Oil or Gas)	County RIO ARRIB METHOD OF PROD (Flow or Art. Lift)				
Upper Completion	MESAVERDE		Gas	Flow	Tubing			
Lower Completion	DAKOTA		Gas	Flow	Tubing			
		PRE-FLOW SHUT-	IN PRESSURE DATA					
Upper	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
Completion	06/07/2000	120 Hours	280	Salvani, (
Lower	00/01/2000	720 110410						
Completion	06/07/2000	72 Hours	615 EST NO. 1					
Commenced	at (hour.date)*	06/10/2000		g (Upper or Lower) L	OWER			
TIME	LAPSED TIME	PRESSURE	PROD. ZONE		OVVER			
(hour.date)	SINCE*	Upper Completion Lower Com			MARKS			
6/11/200	96 Hours	280 161		Turn on lower zone.				
6/12/200	120 Hours	282 160	••					
					JUN 2000			
				\$				
Production rate	during test							
Oil:	BOPD based on	Bbls. in	Hours.	Grav.	GOR			
Gas:		MCFPD; Tested thru (Orifice or Meter):						
		MID-TFST SHUT-	IN PRESSURE DATA					
Upper Completion	Hour. date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
3619101 347	9101 347 (Continue on reverse side)							

FLOW TEST NO. 2

Commenced at (hour, da	ate)**		Zone producing (Upper or Lower):			
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	DEMARKS	
		Upper Completion	Lower Completion	on TEMP.	REMARKS	
	-		-			
· 						
	<u> </u>	L	L			
Production rate du	ring test					
Oil:	BC	OPD based on	Bbls. in	1 Hours	Grav GOR	
Gas:		MCFPI	D: Tested thru (C	Orifice or Meter):		
Remarks:						
				-		
I hereby certify that	t the information he	rein contained is true	and complete to	o the best of my knowled	ge.	
	.IIIN 9	7 2000 is		. 		
	•			Operator Burling	ton Resources	
	il Conservation Divi			By More	Chara a	
ORIGENAL	SIGNED BY CHAR	LET MAN		By Aldrio	uz.	
Ву				Title Operations A	_ Associate	
96	PATTY OIL & GAS !	NSPECTOR, DIST.	<u></u>	F		
Title				Date Monday, June 26, 2000		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shat-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual competion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form. Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).