

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-078997

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 #52M

9. API Well No.

30-039-25677

10. Field and Pool, or exploratory Area

Blanco Mesaverde
and Basin Dakota

11. County or Parish, State

Rio Arriba, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit I, 1456' FSL & 851' FEL
Section 15, T30N, R5W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other 4-1/2" casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/8/97

RIH w/6-1/4" bit and tagged cement @ 3768' and drilled cement to 3808'. Drilled from 3808'-8013' (TD). POOH. RU Blue jet & ran GR/Temperature log from 5200'-8013'. RU & RIH w/4-1/2" 11.6# N-80 LT&C casing and set 8001'.

RU BJ to cement. Pumped 7 bbls H2O & 35 bbls of gel water ahead. Lead cement pumped - 315 sx (428 cu ft) 50% POZ, 50% Class "B" cement + 4% gel (Bentonite) + 5% FL-62 + 67.2% H2O @ 13.4 ppg & 1.36 yield. Tail cement - 100 sx (150 cu ft) Class "H" cement + 35% Silica Flour + 1/8% FL-62 + .25/sx Cello-Flake + 52.72% H2O & 15.9 ppg & 1.50 yield. Displaced w/122.5 bbls of 1% KCl water & bumped plug.

RD BJ. ND BOPs & set slips. NU WH. Test to 200 psi for 3 min. & 3,000 for 10 min. OK. RD & MO 5/14/97.

14. I hereby certify that the foregoing is true and correct

Signed

Title Regulatory Assistant

Date 5-14-97

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States a false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NWCCD

FARMINGTON DISTRICT OFFICE
BY