Stabilized? (Yes or No)

30-039-25683

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10:01:78

This form is not to be used for reporting nacker leakage tests in Southeast New Mexico

Completion

Lower Completion 3636302

351

Hour, date shut-in

Length of time shut-in

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well Operator BURLINGTON RESOURCES OIL & GAS CO. SAN JUAN 30-6 UNIT No. 36A Location **RIO ARRIBA** 030N 006W County Twp. Rge. of Well: Unit Sect 08 TYPE OF PROD METHOD OF PROD. PROD. MEDIUM NAME OF RESERVOIR OR POOL (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper Gas Flow Tubing **MESAVERDE** Completion Lower DAKOTA Gas Flow Tubing Completion PRE-FLOW SHUT-IN PRESSURE DATA SI press. psig Stabilized? (Yes or No) Length of time shut-in Upper Hour, date shut-in Completion 120 Hours 05/25/2001 300 Lower Completion 910 05/25/2001 72 Hours FLOW TEST NO. 1 05/28/2001 Zone producing (Upper or Lower) LOWER Commenced at (hour.date)\* PROD. ZONE TIME LAPSED TIMI PRESSURI TEMP SINCE\* REMARKS (hour.date) Upper Completion Lower Completion 305 250 05/29/2001 96 Hours 308 245 05/30/2001 120 Hours Production rate during test **GOR** BOPD based on Grav Oil Hours Gas MCFPD: Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Stabilized? (Yes or No) Length of time shut-in SI press. psig Hour, date shut-in Upper

SI press. psig

(Cortinue on reverse side)

## FLOW TEST NO 2

mmenced at (hour, date)**				Zone producing (Upper or Lower):	
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	
		Upper Completion	Lower Completion	TEMP.	REMARKS
	<del> </del>				
<del>_</del>					
	<b>†</b>				
<del></del>		<u> </u>			
luction rate du	iring tesi				
	<i>D</i>	ODD I			
BOPD based on					
		MCFP	D: Tested thru (Orific	ce or Meter):	
ITKS:					
الماء الكائسين المعادد	and the state of t				
coy certify th	at the information he	rein contained is true 2001	and complete to the	best of my knowledge	
roved	edAUG 2 4 2001			perator <b>Burlingto</b>	1 Resources
iew Mexico O	oil Conservation Div	ision		01 1	7.
<b>GRIE</b>	NAL SIGNED BY	HARLE T. PERSON	i <del>.</del>	Mars L	Lay:
		T. PRINT	т	itle <u>Operations As</u>	C/ Societo
		AS INSPECTOR, PIST		Operations As	sociate

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Sught tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or tracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Dixison:
- 2.—At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-near pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for E-lihours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be thice hours.
- 5 Following completion of Flow Test No.  $|\hat{l}|$  the well shall again be shut-in: in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated ouring Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period at least one time during each flow period tat approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. It a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)