

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.
SF-079012
6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 2510' FNL & 1850' FEL
Section 4, T30N, R6W

7. If Unit or CA, Agreement Designation
San Juan 31-6 Unit
8. Well Name and No.
SJ 31-6 #205R
9. API Well No.
30-039-25691
10. Field and Pool, or exploratory Area
Basin Fruitland Coal
11. County or Parish, State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other 7" casing report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH w/8-3/4" bit and workstring and tagged cement 347'. Drilled out 25' of cement. Drilled ahead to 3180'. Circulated & conditioned hole. POOH. RIH w/7" 20# J-55 ST&C 8rd casing and set at 3160'. RU BJ to cement. Pumped 20 bbls mudflush; 5 bbls H2O spacer; Lead slurry - 450 sx (945 cu ft) 65/35 Class B POZ w/5#/sx gilsonite, 1/4#/sx cello-flake, 12% gel (bentonite) mixed @ 12 ppg w/2.21 yield. Tail slurry; 150 sx (180 cu ft) Class B cement w/5#/sx gilsonite, 1/4#/sx cello-flake, .3% FL-62, 2% CaCl2 mixed @ 15.6 ppg w/1.20 yield. Dropped plug & displaced w/128 bbls H2O, bumped plug @ 1900 psi. 18 bbls (101 cu ft) cement returns. RD BJ. ND BOPs and set slips. WOC 4 hours. Pressure test - 200 psi for 3 min. and 1500 psi for 10 min. Good test.

14. I hereby certify that the foregoing is true and correct

Signed

Patsy Clugston

Title Regulatory Assistant

Date

6-23-97

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JUN 27 1997

* See Instruction on Reverse Side

NMOCD

FARMINGTON DISTRICT OFFICE
5-11-97