

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Phillips Petroleum Company

3. Address and Telephone No.  
5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Unit P, 1090' FSL & 790' FEL  
Section 14, T30N, R5W

5. Lease Designation and Serial No.

SF-080538

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 Unit 29A

9. API Well No.

30-039-25707

10. Field and Pool, or exploratory Area

Blanco Mesaverde  
and Basin Dakota

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other 7" casing report  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

GIH w/8-3/4" bit and drilled 60' of cement to shoe. Drilled ahead to 4200'. Circ. mud flush & conditioned hole. RIH w/7" 20# J-55 casing & set @ 4194'. RU BJ to cement. Pumped Lead Cement - 430 sx (1236 cf) Class B, 5#/sx Hi-Seal, 3% SM, 1/4#/sx cello-flake mixed @ 11.4 ppg w/ yield of 2.90 ft<sup>3</sup>/sx. Tail - pumped 150 sx (180 cf) Class B, 1/4#/sx cello-flake, 0.3% FL-62 & 2% CaCl<sub>2</sub> mixed @ 15.6 ppg w/ yield of 1.20 ft<sup>3</sup>/sx. Displaced w/170 bbls water @ 6 bpm. Bumped plug @ 300 - 200 # @ 2143 hrs on 8/15/97. No cement returns to surface. RD BOPs & set slips. Test casing to 200 psi for 3 min. and 1500 psi for 30 min. - OK. Ran temperature survey. Showed Top of Cement @ 850'.

RECEIVED  
AUG 25 1997

OIL CON. DIV.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Regulatory Assistant

Date

8-20-97

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

AUG 22 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE

BY

NMOCH