

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Hwy. 64, NBU 3004, Farmington, NM 87401 (505) 599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit M, 550' FSL & 485' FWL
Section 11, T30N, R5W

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-080538

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 Unit 257

9. API Well No.

30-039-25718

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other As Per NTL-FRA-90-1

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion or V Completion or Recompletion Report and Log for

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 9/7/97 Time Started: 1045 hrs Time Completed: 1200 hrs.

Hole Size 8-3/4" Casing Size 7"m 20# J-55 New; Casing Set at 3112' ft.

Turbo Centralizers at 2684', 2664', 2497'

Spring Type Centralizers 3102', 3083', 3040', 2954', 2880', 340',

Mud Flush 20 Bbls, Spacer 10 Fresh Water.

Stage 1:

Lead Slurry 450 sx 65/35 B POZ, 12% Gel, 5#/sx gilsonite, 1/4#/sx cello-flake (995 cu ft - 2.21 yield)

Mid Slurry

Tail Slurry 150 sx Cl B, 2% CaCl2, 1/4#/sx cello-flake, 5#/sx gilsonite

Stage 2: 0.3 FL-62 (180 cu ft - 1.20 yield)

Lead Slurry

Mid Slurry

Tail Slurry

Volume Cement Circulated 20 Bbls/Sacks 51 Displaced Plug with 125 Bbls Fresh Water

Average Pressure 200 PSI, Average Rate 6.5 BPM, Bumped Plug with 800 PSI.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Regulatory Assistant

Date

9-10-97

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

SEP 10 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

RV

FARMINGTON DISTRICT OFFICE