119000

## UNITED STATES

## DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVE.

	ices and Reports on Wells/22	5.	Lease Number
. Type of Well GAS	070 <sub>171</sub>	6.	NM-02151B If Indian, All. or Tribe Name
. Name of Operator	<del></del>	7.	
BURLINGTON			San Juan 30-6 Unit
. Address & Phone No. of Operat	& GAS COMPANY	8.	Well Name & Number San Juan 30-6 U #93
PO Box 4289, Farmington, NM		9.	API Well No. 30-039-25806
4. Location of Well, Footage, Section 1655' FNL, 880' FWL, 880' FW		10.	Field and Pool
	.33, T-30-N, R-7-W, NMPM	11.	Blanco Mesaverde County and State Rio Arriba Co, NM
Final Abandonment	Casing Repair Wate Altering Casing Conv	ersion to	Injection
Final Abandonment  Describe Proposed or Compl	Altering Casing Conv _X_ Other - Spud, casing and	ersion to	Injection
Describe Proposed or Comple  6-13-98 MIRU. Spud well @ clean. TOOH  6-14-98 TIH w/5 jts 9 5/8 Class "B" nea (201 cu ft). BOP & csg to	Altering CasingConv _X_ Other - Spud, casing and leted Operations	cement  cement  227'.  KB. Cmtd 0.25 pps WOC. No.	Circ hole  w/170 sx Flocele U BOP. PT
6-13-98 MIRU. Spud well @ clean. TOOH 6-14-98 TIH w/5 jts 9 5/8 Class "B" nea (201 cu ft). BOP & csg to	Altering Casing ConvX_ Other - Spud, casing and Leted Operations  10:00 p.m. 6-13-98. Drill to . 3" 32.3# WC-50 csg, set @ 220' at cmt w/4% calcium chloride,         Circ 15 bbl cmt to surface. 0 600 psi/30 min., OK. Drilli	cement  cement  227'.  KB. Cmtd 0.25 pps WOC. No.	Circ hole  W/170 sx Flocele U BOP. PT
6-13-98 MIRU. Spud well @ clean. TOOH 6-14-98 TIH w/5 jts 9 5/8 Class "B" nea (201 cu ft). BOP & csg to	Altering Casing ConvX_ Other - Spud, casing and Leted Operations  10:00 p.m. 6-13-98. Drill to . 3" 32.3# WC-50 csg, set @ 220' at cmt w/4% calcium chloride,         Circ 15 bbl cmt to surface. 0 600 psi/30 min., OK. Drilli	ersion to cement 0 227'. KB. Cmtd 0.25 pps WOC. No ng ahead lean. TO	Circ hole  W/170 sx Flocele U BOP. PT OOH.
6-13-98 MIRU. Spud well @ clean. TOOH 6-14-98 TIH w/5 jts 9 5/8 Class "B" nea (201 cu ft). BOP & csg to 6-16-98 Drill to intermed	Altering CasingConv _X_ Other - Spud, casing and leted Operations  10:00 p.m. 6-13-98. Drill to . 3" 32.3# WC-50 csg, set @ 220' at cmt w/4% calcium chloride,     Circ 15 bbl cmt to surface. o 600 psi/30 min., OK. Drilli liate TD @ 3353'. Circ hole ci	ersion to cement 0 227'. KB. Cmtd 0.25 pps WOC. No. ng ahead lean. TO	Circ hole  W/170 sx Flocele U BOP. PT  OH.  JUL 1 3 1938  OHL COM DIV