## STATE OF NEW MEXICO \_ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

in Southeast New Mexico NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST													
Operate	or V	Purlingta	Lisrue	'W Lease (	San	Juan	v 30-6	We No	394				
Location of Well: Unit Sec. 13 Twp. 30				Lease San Ju Rgc. 06			County						
NAME OF RESERVOIR OR POOL				TYPE OF	TYPE OF PROD. (Oll or Gee)		METHOD OF PROD. (Flow or Art. Lill)		PROD. MEDIUM (Tbg. or Cag.)				
Upper Completion Mesa Oude				gas	Gas		Glow		189				
Campletion allota				gas	gas		How		189				
PRE-FLOW SHUT-IN PRESSURE DATA													
Upper Completio	Hour, date s	t Delivery	-18-98	8 - 98 SI press, paig, 678			Stabilized? (Yes or No)						
Lower Completion WA Del		Length of time shut-	in -18-98	St press, paig 2820			Stabilized? (Yes or No)						
				FLOW TEST	NO. 1								
Consmenced at (hour, date) * 9-18-98					Zone producing (Upper		per or Lower):	Z	epper				
TIME LAPSED TIME (hour, date) SINCE*		LAPSED TIME SINCE#	PRESSI Upper Completion	Lower Completion	I .	PROD. ZONE TEMP.		REMARKS					
9-19-98			447	2840					The same of the sa				
9-20-98			392	2860			PECE		700				
							S	EP	AED				
·						i.	@[][] (G		1998				
							10	MI S	DUM				
				·				1-1					
Production rate during test													
Oil:BOPD based onBbls. inHoursGravGOR													
Gas: MCFPD; Tested thru (Orifice or Meter):													
			MID-TES	T SHUT-IN PE	ESSURE I	ATA							
Upper Completion	Hour, date shut-in Length o			<del></del>		SI press, peig		Stabilized? (Yes or No)					
Lower	Lower Hour, date shut-in		Length of time shut-in	Length of time shut-in		St press. psig		Stabilized? (Yes or No)					

FLOW TEST NO. 2

menced at (hour, d	ate) * *			Zone producing (Upp	per or Lower:
PRESSURE			ISURE	PROD. ZONE	REMARKS
TIME (hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	
				ł	
		ļ	<del> </del>	<del></del>	
		<del> </del>			
<u> </u>					1
			1		Į.
		<u> </u>		<del></del>	
					Grav GOR r):
a e lea .					
arks:					
	<del>-</del>				
eby certify	that the informat	ion herein contair	ned is true and co	mplete to the be	st of my knowledge.
•	SEP 2	סענו ל	19 (	Operator 30	reator Esources
roved	Oil Conservation	2 1770 Division	^/ `	2/	
EM DIEXILO C		<del> </del>	I	By	ores (Dias)
ON	HAL SIGNED BY	CHARLIE T. PE	M 	Title GOVA	Just Associate 21-98
NEP	UTY OIL & GAS IN	ISPECTOR, DIST.	<b>3</b>	Date 9-	21-98
, V.,	CIVE II				

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).