

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Taurus Exploration U.S.A., Inc.

3. Address and Telephone No.

2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

807' FSL, 692' FEL, Sec. 18, T30N, R4W, N.M.P.M.

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-079485-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit #41M

9. API Well No.

30-039-25917

10. Field and Pool, or exploratory Area

Blanco MV / Basin DK

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Int Casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/27/98 Ran 107 joints 7 5/8", 26.40#, J-55, STC casing 4619' set at 4631'. DV tool at 3896'. Cemented first stage with 225 sks Class B w/ 2% CaCL2, 1/4# Flocele/sk and 10# Gilsonite/sk. (315 cu. ft.). Plug down 2:45pm 8/27/98. Open DV tool. Try to circulate no returns. Cemented 2nd stage with 910 sks 65/35 Poz with 6% gel, 2% CaCL2, 1/4# Flocele/sk and 10# Gilsonite/sk followed by 100 sks Class B w/ 2% CaCL2, 1/4# Flocele/sk and 10# Gilsonite/sk. (1869 cu. ft.). Gained Circ. to surface during displacement. Plug down 10:00pm 8/27/98. Ran temp survey. TOC - 2165'. Tested csg to 1200 psi-OK.

14. I hereby certify that the foregoing is true and correct

Signed 

Title Production Superintendent

Date 9/10/98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

44000

FARMINGTON DISTRICT OFFICE

BY

90 OCT 01 1998